

Specification: MOS/CV1900/Issue 4 Dated:- 3.9.46 To be read in conjunction with K1001	<u>SECURITY</u>	
	<u>Specification</u> Restricted	<u>Valve</u> Unclassified

→ indicates a change

<u>TYPE OF VALVE</u> :- Variable $\mu$ H.F. Pentode		<u>MARKING</u>		
<u>CATHODE</u> :- Indirectly heated		See K1001/4		
<u>ENVELOPE</u> :- Glass - unmetallised		Additional marking:- 6D6		
<u>PROTOTYPE</u> :- 6D6				
<u>RATING</u>		Note	<u>BASE</u> USS6	
Heater voltage (V)	6.3	A	Pin	Electrode
Heater circuit (A)	0.3		1	Heater
Max. anode voltage (V)	250		2	Anode
Max. screen voltage (V)	100		3	Screen grid
Mutual conductance (mA/V)	1.6		4	Suppressor grid
<u>CAPACITANCES (pF)</u>			5	Cathode
Cag (max.)	0.01		6	Heater
Cae	6.5		TC	Control grid
Cge	4.75		<u>TOP CAP</u>	
<u>NOTES</u>		<u>DIMENSIONS</u>		
A. Measured at $V_a = 250$ , $V_{g2} = 100$ , $V_{g3} = -3$ .		See K1001/AI/D1		
		Dimension	Min.	Max.
		A mm	119	126
	B mm	-	40	

To be performed in addition to those applicable in K1001

	Test conditions					Test	Limits		No. tested
							Min.	Max.	
a	See K1001/AIII					<u>Capacitances (pF)</u>			
	Links to H.P.	Links to L.P.	Links to E.						
	2	TC <sub>1</sub>	1,3,4,5,6,7,8,9,10, TC <sub>2</sub>			(i) C <sub>ag</sub>	-	0.01	T.A.
	2	1,3,4,5,6	7,8,9,10, TC <sub>1</sub> ,TC <sub>2</sub>			(ii) C <sub>ac</sub>	5.5	7.5	6 per week
TC <sub>1</sub>	1,3,4,5,6	2,7,8,9,10,TC <sub>2</sub>			(iii) C <sub>ge</sub>	4.0	5.5		
b	V <sub>h</sub>	V <sub>a</sub>	V <sub>G2</sub>	V <sub>G1</sub>	V <sub>G3</sub>	I <sub>h</sub> (A)	0.27	0.33	100% or 8
	6.3	-	-	-	-				
c	6.3	250	100	-3	0	I <sub>a</sub> (mA)	5.8	10.4	100%
d	6.3	250	100	-3	0	I <sub>G2</sub> (mA)	0.1	3.2	100%
e	6.3	250	100	-3	0	g <sub>m</sub> (mA/V)	1.35	1.9	100%
f	6.3	250	100	-3	0	Rev I <sub>G1</sub> (uA)	-	1.0	100%
g	6.3	250	100	-30	0	I <sub>a</sub> (mA)	-	1.0	100%