Oscillograph Tube

ELECTROSTATIC DEFLECTION FLECTROSTATIC FOCUS For Extremely Low-Speed Recurrent, or Medium-Speed Non-Recurrent Image Displays The 5UP7 is the same as the 5UP1 except for the following items: GENERAL Phosphor (For curves, see front of this section). Yellowish-Green Phosphorescence. Persistence^a,b

5UP11

Oscillograph Tube

ELECTROSTATIC DEFLECTION

	FUI	FILE	rog	$u \mu$	1111	C	ne	CO	r u	ιπ	В	un	и	νı	Su	uι	U	US	e i	vaiio	us		
The	5UP 1	1 is	the	sam	ie d	18	t h	e :	5 <i>UF</i>	1	e x	c c e	ep t		for	٠ ،	the	e f	o l	lowin	git	ems	:
									GE	ENE	ER/	۱L											
Pho	sphor	(Fo	r c	urv	es,	s	ee	fı	ron	١t	of	t	nis	; ;	sec	t i	or	1)				PΙ	I
F	luore	scen	ce																	Actir	ic-	B1u	e
Pl	hosphi	ores	cen	ce,																Actir	iic-	B1 u	e
	Pers	iste	ncei	a,b																Mediu	ım-S	hor	t

5UP31

Oscillograph Tube

ELECTROSTATIC DEFLECTION

The SUP31 is the same	as the	DUPI	except	jor the	followin,	g items:
		GE	NERAL			
Phosphor (For curve	es see	type	7VP31)		å v n è ş	P31
Fluorescence						
Phosphorescençe.	s 9 9	9 8	6 s s z	s s 6	x & 0 0 x	Green
Persistence ^b .	4 2 4		. Medium	⊩Short [©]	(Approx.	38 μ sec)
a						

For Low- or Medium-Speed Non-Recurring Image Displays

Phosphorescence may have a useful brightness for over a minute under conditions of adequate excitation and low-ambient illumination.



ELECTROSTATIC FOCUS

ELECTROSTATIC FOCUS

Persistence of useable brightness can be obtained with an anode-No.2 voltage of as low as $1500\ \mathrm{volts}$.

Time for initial brightness to decay to 10% point.