

Picture Tube

SHORT RECTANGULAR GLASS TYPE
LOW-VOLTAGE ELECTROSTATIC FOCUS
LOW GRID-No.2 VOLTAGE

ALUMINIZED SCREEN
114° MAGNETIC DEFLECTION
CATHODE-DRIVE TYPE

With Heater Having Controlled Warm-Up Time

GENERAL DATA

Electrical:

Heater Current at 6.3 volts	450 ± 10%	ma
Heater Warm-Up Time (Average)	11	seconds
Direct Interelectrode Capacitances:		
Grid No.1 to all other electrodes	6	μμf
Cathode to all other electrodes	5	μμf
External conductive coating to ultor.	{ 1900 max. 1400 min.	μμf
Electron Gun.		Type Requiring No Ion-Trap Magnet


Optical:

Faceplate	Filterglass
Light transmission (Approx.)	78%
Phosphor (For curves, see front of this section)	P4—Sulfide Type, Aluminized

Mechanical:

Operating Position.	Any
Weight (Approx.)	14 lbs
Overall Length.	11-3/8" ± 1/4"
Neck Length	4-1/8" ± 1/8"
Projected Area of Screen.	172 sq. in.
External Conductive Coating:	
Type.	Regular Band
Contact area for grounding.	Near Reference Line
For Additional Information on Coatings and Dimensions:	
See <i>Picture-Tube Dimensional-Outlines</i> and <i>Bulb J149 A</i> sheets at the front of this section	
Cap	Recessed Small Cavity (JEDEC No.J1-21)
Base.	Special 6-Pin (JEDEC No.B6-214)
Basing Designation for BOTTOM VIEW.	7FA

Pin 2—Cathode
Pin 3—Heater
Pin 4—Heater
Pin 5—Grid No.1
Pin 6—Grid No.4
Pin 7—Grid No.2



Cap—Ultor
(Grid No.3,
Grid No.5,
Collector)
C—External
Conductive
Coating



19AJP4

Maximum and Minimum Ratings, Design-Maximum Values:

ULTOR-TO-GRID-No.1 VOLTAGE.	{ 19800 max.	volts
	{ 12000 min.	volts
GRID-No.4-TO-GRID-No.1 (FOCUSING) VOLTAGE:		
Positive value.	1100 max.	volts
Negative value.	500 max.	volts
GRID-No.2-TO-GRID-No.1 VOLTAGE.	{ 70 max.	volts
	{ 40 min.	volts
CATHODE-TO-GRID-No.1 VOLTAGE.	100 max.	volts
HEATER VOLTAGE.	{ 7 max.	volts
	{ 5.8 min.	volts
PEAK HEATER-CATHODE VOLTAGE:		
Heater negative with respect to cathode:		
During equipment warm-up period		
not exceeding 15 seconds.	410 max.	volts
After equipment warm-up period. . . .	180 max.	volts
Heater positive with respect to cathode.		
	180 max.	volts

Typical Operating Conditions:

With ultor-to-grid-No.1 voltage of	14500	volts
and grid-No.2-to-grid-No.1 voltage of	50	volts
Grid-No.4-to-Grid-No.1 Voltage for focus .	0 to 500	volts
Cathode-to-Grid-No.1 Voltage for visual extinction of focused raster. . .	31 to 49	volts

Maximum Circuit Values:

Grid-No.1-Circuit Resistance.	1.5 max.	megohms
---------------------------------------	----------	---------

For X-radiation shielding considerations, see sheet
X-RADIATION PRECAUTIONS FOR CATHODE-RAY TUBES
at front of this section

