

Picture Tube

RECTANGULAR GLASS TYPE
LOW-VOLTAGE ELECTROSTATIC FOCUS

ALUMINIZED SCREEN
72° MAGNETIC DEFLECTION

GENERAL DATA

Electrical:

Heater Current at 6.3 volts	600	ma
Direct Interelectrode Capacitances:		
Grid No.1 to all other electrodes	6	μmf
Cathode to all other electrodes	5	μmf
External conductive coating to ultor.	{2500 max. μmf 2000 min. μmf	
Electron Gun.	Ion-Trap Type Requiring External Single-Field Magnet	


Optical:

Faceplate, Spherical.	Filterglass
Light transmission (Approx.).	74%
Phosphor (For curves, see front of this section).	P4—Sulfide Type, Aluminized

Mechanical:

Operating Position.	Any
Weight (Approx.).	24 lbs
Overall Length.	23-1/32" $\pm$ 3/8"
Neck Length.	7-1/2" $\pm$ 3/16"
Projected Area of Screen.	262 sq. in.
External Conductive Coating:	
Type.	Special
Contact area for grounding.	Near Reference Line
For Additional Information on Coatings and Dimensions:	
See <i>Picture-Tube Dimensional-Outlines</i> and <i>Bulb J171 B/F</i> sheets at the front of this section	
Cap	Recessed Small Cavity (JEDEC No.J1-21)
Base.	Small-Shell Duodecal 6-Pin, Arrangement 1, (JEDEC Group 4, No.B6-63)
Basing Designation for BOTTOM VIEW.	12L

- Pin 1 - Heater
- Pin 2 - Grid No.1
- Pin 6 - Grid No.4
- Pin 10 - Grid No.2
- Pin 11 - Cathode
- Pin 12 - Heater



- Cap - Ultor
(Grid No.3,
Grid No.5,
Collector)
- C - External
Conductive
Coating



21AVP4B

Maximum Ratings, Design-Maximum Values:

ULTOR VOLTAGE	22000 max.	volts
GRID-No.4 (FOCUSING) VOLTAGE:		
Positive value.	1100 max.	volts
Negative value.	550 max.	volts
GRID-No.2 VOLTAGE	550 max.	volts
GRID-No.1 VOLTAGE:		
Negative peak value	220 max.	volts
Negative bias value	155 max.	volts
Positive bias value	0 max.	volts
Positive peak value	2 max.	volts
PEAK HEATER-CATHODE VOLTAGE:		
Heater negative with respect to cathode:		
During equipment warm-up period not exceeding 15 seconds.	450 max.	volts
After equipment warm-up period.	200 max.	volts
Heater positive with respect to cathode.	200 max.	volts

Typical Operating Conditions:

With ultor voltage of	18000	volts
and grid-No.2 voltage of	300	volts
Grid-No.4 Voltage for focus	-72 to +396	volts
Grid-No.1 Voltage for visual extinction of focused raster.	-28 to -72	volts

Maximum Circuit Values:

Grid-No.1-Circuit Resistance.	1.5 max.	megohms
---------------------------------------	----------	---------

For X-radiation shielding considerations, see sheet
X-RADIATION PRECAUTIONS FOR CATHODE-RAY TUBES
at front of this section

