

21AWP4A

Picture Tube

NO ION-TRAP MAGNET REQUIRED

**RECTANGULAR GLASS TYPE
MAGNETIC FOCUS**

**ALUMINIZED SCREEN
72° MAGNETIC DEFLECTION**

Electrical:

Direct Interelectrode Capacitances:

Cathode to all other electrodes.	5	pf
Grid No.1 to all other electrodes.	6	pf
External conductive coating to anode.	{ 2500 max. 2000 min.	{ pf pf
Heater Current at 6.3 volts.	600 ± 30	ma
Heater Warm-up time (Average).	11	seconds
Electron Gun	Type Requiring No Ion-Trap Magnet	

Optical:

Phosphor (For curves, see front of this Section).	P4—Sulfide Type, Aluminized
Faceplate, Spherical	Filterglass
Light transmission (Approx.)	74%
Surface of Protective Window	Treated to reduce specular reflection

Mechanical:


Weight (Approx.)	24 lbs
Overall Length	23.031" ± .375"
Neck Length.	7.500" ± .188"
Projected Area of Screen	262 sq.in.
External Conductive Coating:	

Type Regular-Band
Contact area for grounding. Near Reference Line
For Additional Information on Coatings and Dimensions:

See *Picture-Tube Dimensional-Outlines and Bulb J171 B/F* sheets
at front of this section

Cap.	Recessed Small Cavity (JEDEC No.J1-21)
Base	Small-Shell Duodecal 5-Pin (JEDEC Group 4, No.B5-57)
Basing Designation for BOTTOM VIEW.	12N

- Pin 1—Heater
Pin 2—Grid-No.1
Pin 10—Grid No.2
Pin 11—Cathode
Pin 12—Heater
Cap—Anode (Grid No.3,
Screen,
Collector)
C—External
Conductive Coating



Maximum and Minimum Ratings, Design-Maximum Values:

*Unless otherwise specified, voltage values
are positive with respect to cathode*

Anode Voltage.	20000 max.	volts
Grid-No.2 Voltage.	550 max.	volts



RADIO CORPORATION OF AMERICA
Electronic Components and Devices
Harrison, N. J.

DATA
4-65

21AWP4A

Grid-No.1 Voltage:

Negative peak value.	220 max.	volts
Negative bias value.	155 max.	volts
Positive bias value.	0 max.	volts
Positive peak value.	2 max.	volts
Heater Voltage	{ 6.9 max.	volts
	{ 5.7 min.	volts

Peak Heater-Cathode Voltage:

Heater negative with respect to cathode:		
During equipment warm-up period not exceeding 15 seconds.	450 max.	volts
After equipment warm-up period	200 max.	volts
Heater positive with respect to cathode:		
Combined AC and DC voltage	200 max.	volts
DC component	100 max.	volts

Typical Operating Conditions for Cathode-Drive Service:

Unless otherwise specified, voltage values are positive with respect to grid No.1

Anode Voltage.	18000	volts
Grid-No.2 Voltage.	400	volts
Cathode Voltage for visual extinction of focused raster.	36 to 78	volts

Maximum Circuit Values:

Grid-No.1-Circuit Resistance	1.5 max.	megohms
--	----------	---------

For X-radiation shielding considerations, see sheet
X-RADIATION PRECAUTIONS FOR CATHODE-RAY TUBES
at front of this Section

