23BTP4

Picture Tube

BI-PANEL RECTANGULAR GLASS TYPE — ALUMINIZED SCREEN
LOW-VOLTAGE ELECTROSTATIC FOCUS — 92° MAGNETIC DEFLECTION

The 23BTP4 is the same as the 23YP4 except for the following item:

Maximum and Minimum Ratings, *Design-Maximum Values:*

Anode (Ultor) Voltage. . . . . {25000 max. volts / 15000 min. volts

23CBP4

Picture Tube

BI-PANEL RECTANGULAR GLASS TYPE — ALUMINIZED SCREEN
LOW-VOLTAGE ELECTROSTATIC FOCUS — 110° MAGNETIC DEFLECTION

The 23CBP4 is the same as the 23BQP4 except for the following item:

Optical:

Surface of Protective Panel. . . . . .Treated to reduce specular reflection

23CGP4

Picture Tube

CONTROLLED HEATER WARM-UP TIME

RECTANGULAR GLASS TYPE — ALUMINIZED SCREEN
LOW-VOLTAGE ELECTROSTATIC FOCUS — 92° MAGNETIC DEFLECTION

The 23CGP4 is the same as the 23AHP4 except for the following item:

Electrical:

Heater Current at 6.3 volts. . . . . 450 ± 20 ma