

23BTP4

Picture Tube

BI-PANEL RECTANGULAR GLASS TYPE
LOW-VOLTAGE ELECTROSTATIC FOCUS

ALUMINIZED SCREEN
92° MAGNETIC DEFLECTION

The 23BTP4 is the same as the 23YP4 except for the following item:

Maximum and Minimum Ratings, Design-Maximum Values:

Anode (Ultor) Voltage.	{ 25000 max. volts
	{ 15000 min. volts

23CBP4

Picture Tube

BI-PANEL RECTANGULAR GLASS TYPE
LOW-VOLTAGE ELECTROSTATIC FOCUS

ALUMINIZED SCREEN
110° MAGNETIC DEFLECTION

The 23CBP4 is the same as the 23BQP4 except for the following item:

Optical:

Surface of Protective Panel.	Treated to reduce specular reflection
--------------------------------------	---------------------------------------

23CGP4

Picture Tube

CONTROLLED HEATER WARM-UP TIME

RECTANGULAR GLASS TYPE
LOW-VOLTAGE ELECTROSTATIC FOCUS

ALUMINIZED SCREEN
92° MAGNETIC DEFLECTION

The 23CGP4 is the same as the 23AHP4 except for the following item:

Electrical:

Heater Current at 6.3 volts.	450 ± 20 ma
--------------------------------------	-------------

