



OD3 VOLTAGE REGULATOR

GLOW-DISCHARGE TYPE

GENERAL DATA

Electrical:

Cathode Cold

Mechanical:

Mounting Position Any

Maximum Overall Length 4-1/8"

→ Seated Length 3-3/8" ± 3/16"

Maximum Diameter 1-9/16"

Dimensional Outline See General Section

→ Weight (Approx.) 1.3 oz

Bulb ST-12


→ Base Small-Shell Octal 6-Pin (JETEC No. B6-3)

Basing Designation for BOTTOM VIEW 4AJ

Pin 1—No Connection

Pin 2—Cathode

Pin 3—Jumper▲



Pin 5—Anode

Pin 7—Jumper▲

Pin 8—No Connection

Maximum and Minimum Ratings, Absolute Values:

AVERAGE STARTING CURRENT♦ 100 max. ma

DC CATHODE CURRENT { 40 max. ma

→ FREQUENCY { 5 min. ma

AMBIENT-TEMPERATURE RANGE 0 max. cps

-55 to +90 °C

→ Circuit Values:

Shunt Capacitor 0.1 max. μf

Series Resistor See note below

→ CHARACTERISTICS RANGE VALUES FOR EQUIPMENT DESIGN

	Min.	Av.	Max.	
DC Anode-Supply Voltage	185■	—	—	volts
Anode Breakdown Voltage	—	160	185*	volts
Anode Voltage Drop	142●	153	165*	volts
Regulation (5 to 40 ma)	—	4	5.5*	volts

▲ With suitable socket connections, jumper within base acts as a switch to open power-supply circuit when voltage regulator tube is removed from socket.

♦ Averaged over starting period not exceeding 10 seconds. This starting period must be followed by a steady state operating condition of at least 20 minutes, or tube performance will be impaired.

■ Not less than indicated supply voltage should be provided to insure "starting" throughout tube life.

* Maximum individual tube value during useful life.

● Minimum individual tube value during useful life.

The operating considerations and circuit information shown under Type OA3 also apply to Type OD3

→ Indicates a change.