




957

957

DETECTOR, AMPLIFIER, OSCILLATOR

ACORN TYPE

Filament	Coated	
Voltage	1.25	d-c volts
Current	0.05	amp.
Direct Interelectrode Capacitances: ^o		
Grid to Plate	1.2	$\mu\mu\text{f}$
Grid to Filament	0.3	$\mu\mu\text{f}$
Plate to Filament	0.7	$\mu\mu\text{f}$
Overall Length		$1-7/32" \pm 5/32"$
Overall Diameter		$1-3/32" \pm 1/16"$
Bulb }	See Outline in GENERAL SECTION	T-4 $\frac{1}{2}$
Base }		Small Radial 5-Pin
Pin 1 - Filament		Pin 5 - Filament -
Pin 2 - Plate		AA' - Plane of
Pin 3 - Grid		Electrodes
Pin 4 - Filament -		
RCA Socket		Stock No. 9925
Mounting Position		Vertical ^d



Short Part of Bulb: Bottom
BOTTOM VIEW (5BD)

Maximum Ratings Are Design-Center Values

AMPLIFIER

D-C Plate Voltage	135 max.	volts
Characteristics— Class A₁ Amplifier:		
D-C Plate Voltage	135	volts
D-C Grid Voltage*	-5	volts
Amplification Factor	13.5	
Plate Resistance	20800 approx.	ohms
Transconductance	650	μmhos
D-C Plate Current	2	ma.

^o With no external shield.

^d Horizontal operation permitted if plane of electrodes is vertical (plate on edge).

* Under maximum rated conditions, the resistance in the grid circuit should not exceed 0.1 megohm with fixed bias, or 0.5 megohm with cathode bias.

R-F grounding by means of condensers placed close to the tube pins is required if the full capabilities of the 957 for ultra-high-frequency uses are to be obtained.

← Indicates a change.

JUNE 30, 1944

RCA VICTOR DIVISION
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY


DATA

957



957

AVERAGE PLATE CHARACTERISTICS



JUNE 15, 1944

RCA VICTOR DIVISION
RADIO CORPORATION OF AMERICA HARRISON, NEW JERSEY

92CM-6336RI