

OZ4
OZ4-G


OZ4, OZ4-G

FULL-WAVE GAS RECTIFIER

COLD CATHODE TYPE

	<u>OZ4</u>	<u>OZ4-G</u>
Maximum Overall Length	2-5/8"	2-5/8"
Maximum Diameter	1-5/16"	1-1/16"
Bulb	Metal Shell, MT-8	T-7
Base	Small Wafer Octal 6-Pin	Dwarf Shell Octal 5-Pin


Pin 1 - Shell
Pin 2 - No Connection
Pin 3 - Plate #2



BOTTOM VIEW

Pin 5 - Plate #1
Pin 7 - No Connection
Pin 8 - Cathode

Pin 1 - No Connection
Pin 3 - Plate #2
Pin 5 - Plate #1



BOTTOM VIEW

Pin 7 - No Connection
Pin 8 - Cathode

MAXIMUM RATINGS

Starting-Supply Voltage per Plate	300 min. peak	volts
Peak Plate-to-Plate Voltage	1000 max.	volts
Peak Plate Current	200 max.	ma.
D-C Output Current	{ 75 max.	ma.
	{ 30 min.	ma.
D-C Output Voltage	300 max.	volts
Average Dynamic Tube Voltage Drop	24	volts