

Remote-Cutoff Pentode

7-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 3BA6 is the same as the 6BA6 except for the following items:

Heater, for Unipotential Cathode:

Voltage (AC or DC).	3.15	volts
Current	0.6 ± 6%	amp
Warm-up time (Average).	11	sec

3BC5

Sharp-Cutoff Pentode

7-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 3BC5 is the same as the 6BC5 except for the following items:

Heater, for Unipotential Cathode:

Voltage (AC or DC).	3.15	volts
Current	0.6 ± 6%	amp
Warm-up time (Average).	11	sec

PEAK HEATER-CATHODE VOLTAGE:

Heater negative with respect to cathode.	200 max.	volts
Heater positive with respect to cathode.	200 ^a max.	volts

3BE6

Pentagrid Converter

7-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 3BE6 is the same as the 6BE6 except for the following items:

Heater, for Unipotential Cathode:

Voltage (AC or DC).	3.15	volts
Current	0.6 ± 6%	amp
Warm-up time (Average).	11	sec

^a The dc component must not exceed 100 volts.

