

3BZ6

Semiremote-Cutoff Pentode

7-PIN MINIATURE TYPE

For Equipment Having Series Heater-String Arrangement

The 3BZ6 is the same as the 6BZ6 except for the following items:

Heater, for Unipotential Cathode:

Voltage (AC or DC).	3.15	volts
Current	$0.6 \pm 6\%$	amp
Warm-up time (Average).	11	sec

PEAK HEATER-CATHODE VOLTAGE:

Heater negative with respect to cathode.	300 ^a max.	volts
Heater positive with respect to cathode.	200 ^b max.	volts

3CB6

Sharp-Cutoff Pentode

7-PIN MINIATURE TYPE

For Equipment Having Series Heater-String Arrangement

The 3CB6 is the same as the 6CB6-A except for the following items:

Heater, for Unipotential Cathode:

Voltage (AC or DC).	3.15	volts
Current	$0.6 \pm 6\%$	amp

PEAK HEATER-CATHODE VOLTAGE:

Heater negative with respect to cathode.	300 max.	volts
Heater positive with respect to cathode.	200 ^b max.	volts

3CE5

Sharp-Cutoff Pentode

7-PIN MINIATURE TYPE

For Equipment Having Series Heater-String Arrangement

The 3CE5 is the same as the 6CE5 except for the following items:

Heater, for Unipotential Cathode:

Voltage (AC or DC).	3.15	volts
Current	$0.6 \pm 6\%$	amp

^a The dc component must not exceed 200 volts.

^b The dc component must not exceed 100 volts.



RADIO CORPORATION OF AMERICA
Electron Tube Division

Harrison, N. J.

DATA
5-61