

3CF6

Sharp-Cutoff Pentode

7-PIN MINIATURE TYPE

For Equipment Having Series Heater-String Arrangement

The 3CF6 is the same as the 6CF6 except for the following items:

Heater, for Unipotential Cathode:

Voltage (AC or DC)	3.15	volts
Current	$0.6 \pm 6\%$	amp
Warm-up time (Average)	11	sec

PEAK HEATER-CATHODE VOLTAGE:

Heater negative with respect to cathode	300 max.	volts
Heater positive with respect to cathode	200 ^a max.	volts

3CS6

Pentagrid Amplifier

7-PIN MINIATURE TYPE

For Equipment Having Series Heater-String Arrangement

The 3CS6 is the same as the 6CS6 except for the following items:

Heater, for Unipotential Cathode:

Voltage (AC or DC)	3.15	volts
Current	$0.6 \pm 6\%$	amp
Warm-up time (Average)	11	sec

3CY5

Sharp-Cutoff Tetrode

7-PIN MINIATURE TYPE

For Equipment Having Series Heater-String Arrangement

The 3CY5 is the same as the 6CY5 except for the following items:

Heater, for Unipotential Cathode:

Voltage (AC or DC)	2.9	volts
Current	$0.45 \pm 6\%$	amp
Warm-up time (Average)	11	sec

^a The dc component must not exceed 100 volts.