

3CY5
TO
3DT6



3CY5

SHARP-CUTOFF TETRODE

7-PIN MINIATURE TYPE

*Intended for use in equipment having
series heater-string arrangement*

The 3CY5 is the same as the 6CY5 except for the following items:

Heater, for Unipotential Cathode:

Voltage (AC or DC)	2.9	volts
Current	$0.45 \pm 6\%$	amp
Warm-up time (Average)	11	sec

3DK6

SHARP-CUTOFF PENTODE

7-PIN MINIATURE TYPE

*Intended for use in equipment having
series heater-string arrangement*

The 3DK6 is the same as the 6DK6 except for the following items:

Heater, for Unipotential Cathode:

Voltage (AC or DC)	3.15	volts
Current	$0.6 \pm 6\%$	amp
Warm-up time (Average)	11	sec

PEAK HEATER-CATHODE VOLTAGE:

Heater negative with respect to cathode.	300 max. volts
Heater positive with respect to cathode.	200 [▲] max. volts

3DT6

SHARP-CUTOFF PENTODE

7-PIN MINIATURE TYPE

*Intended for use in equipment having
series heater-string arrangement*

The 3DT6 is the same as the 6DT6 except for the following items:

Heater, for Unipotential Cathode:

Voltage (AC or DC)	3.15	volts
Current	$0.6 \pm 6\%$	amp
Warm-up time (Average)	11	sec

[▲] The dc component must not exceed 100 volts.