

3DZ4

Medium-Mu Triode

7-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 3DZ4 is the same as the 6DZ4 except for the following items:

Heater Characteristics and Ratings:

Current.	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450.	3.2	volts
Warm-up time (Average)	11	sec
Peak heater-cathode voltage: Heater negative with respect to cathode	180 max.	volts
Heater positive with respect to cathode	180 ^b max.	volts

3EA5

Sharp-Cutoff Tetrode

7-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 3EA5 is the same as the 6EA5 except for the following items:

Heater Characteristics and Ratings:

Current.	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450.	2.9	volts
Warm-up time (Average)	11	sec

3ER5

High-Mu Triode

7-PIN MINIATURE TYPE

The 3ER5 is the same as the 6ER5 except for the following items:

Heater Characteristics and Ratings:

Current.	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450.	2.8	volts

^b The dc component must not exceed 100 volts.