

4BC8

Medium-Mu Twin Triode

With Semiremote-Cutoff Characteristic

9-PIN MINIATURE TYPE
With Heater Having Controlled Warm-Up Time

The 4BC8 is the same as the 6BC8 except for the following items:

Heater Characteristics and Ratings (Design-Center Values):			
Current.	0.600 ± 0.040	amp	
Voltage (AC or DC) at heater amperes			
= 0.600.	4.2	volts	
Warm-up time (Average)	11	sec	

4BL8

Medium-Mu Triode— Sharp-Cutoff Pentode

9-PIN MINIATURE TYPE
With Heater Having Controlled Warm-Up Time

The 4BL8 is the same as the 6BL8 except for the following items:

Heater Characteristics and Ratings (Design-Center Values):			
Current.	0.600 ± 0.040	amp	
Voltage (AC or DC) at heater amperes			
= 0.600.	4.6	volts	

4BN6

Beam Tube

7-PIN MINIATURE TYPE
With Heater Having Controlled Warm-Up Time

The 4BN6 is the same as the 6BN6 except for the following items:

Heater Characteristics and Ratings (Design-Maximum Values):			
Current.	0.450 ± 0.030	amp	
Voltage (AC or DC) at heater amperes			
= 0.450.	4.2	volts	
Warm-up time (Average)	11	sec	

