

4CS6

Pentagrid Amplifier

7-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 4CS6 is the same as the 6CS6 except for the following items:

Heater Characteristics and Ratings (*Design-Center Values*):

Current	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450	4.2	volts
Warm-up time (Average).	11	sec

4CY5

Sharp-Cutoff Tetrode

7-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 4CY5 is the same as the 6CY5 except for the following items:

Heater Characteristics and Ratings (*Design-Maximum Values*):

Current	0.300 ± 0.020	amp
Voltage (AC or DC) at heater amperes = 0.300	4.5	volts
Warm-up time (Average).	11	sec

4DE6

Sharp-Cutoff Pentode

7-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 4DE6 is the same as the 6DE6 except for the following items:

Heater Characteristics and Ratings (*Design-Maximum Values*):

Current	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450	4.2	volts
Warm-up time (Average).	11	sec

