

# 4DT6

## Sharp-Cutoff Pentode With Two Independent Control Grids

7-PIN MINIATURE TYPE  
With Heater Having Controlled Warm-Up Time

*The 4DT6 is the same as the 6DT6 except for the following items:*

| Heater Characteristics and Ratings (Design-Maximum Values): |               |       |  |
|-------------------------------------------------------------|---------------|-------|--|
| Current . . . . .                                           | 0.450 ± 0.030 | amp   |  |
| Voltage (AC or DC) at heater<br>amperes = 0.450 . . . . .   | 4.2           | volts |  |
| Warm-up time (Average). . . . .                             | 11            | sec   |  |

# 4DT6A

## Sharp-Cutoff Pentode With Two Independent Control Grids

7-PIN MINIATURE TYPE  
With Heater Having Controlled Warm-Up Time

*The 4DT6A is the same as the 6DT6A except for the following items:*

| Heater Characteristics and Ratings (Design-Maximum Values): |               |       |  |
|-------------------------------------------------------------|---------------|-------|--|
| Current . . . . .                                           | 0.450 ± 0.030 | amp   |  |
| Voltage (AC or DC) at heater<br>amperes = 0.450 . . . . .   | 4.2           | volts |  |
| Warm-up time (Average). . . . .                             | 11            | sec   |  |

# 4EH7

## Semiremote-Cutoff Pentode

9-PIN MINIATURE TYPE

*The 4EH7 is the same as the 6EH7 except for the following items:*

| Heater Characteristics and Ratings (Design-Center Values): |               |       |  |
|------------------------------------------------------------|---------------|-------|--|
| Current . . . . .                                          | 0.450 ± 0.030 | amp   |  |
| Voltage (AC or DC) at heater<br>amperes = 0.450 . . . . .  | 4.4           | volts |  |

