



5AM8

DIODE—SHARP-CUTOFF PENTODE

9-PIN MINIATURE TYPE

*Intended for use in equipment having
series heater-string arrangement*

The 5AM8 is the same as the 6AM8 except for the following items:

Heater, for Unipotential Cathodes:

Voltage	4.7		ac or dc volts
Current	0.6		amp
Warm-up time (Average)* .	11		sec

5AN8

MEDIUM-MU TRIODE— SHARP-CUTOFF PENTODE

9-PIN MINIATURE TYPE

*Intended for use in equipment having
series heater-string arrangement*

The 5AN8 is the same as the 6AN8 except for the following items:

Heater, for Unipotential Cathodes:

Voltage	4.7		ac or dc volts
Current	0.6		amp
Warm-up time (Average)* .	11		sec

5AQ5

BEAM POWER TUBE

7-PIN MINIATURE TYPE

*Intended for use in equipment having
series heater-string arrangement*

The 5AQ5 is the same as the 6AQ5 except for the following items:

Heater, for Unipotential Cathode:

Voltage	4.7		ac or dc volts
Current	0.6		amp
Warm-up time (Average)* .	11		sec

PEAK HEATER-CATHODE VOLTAGE:

Heater negative with respect to cathode .	200 max. volts
Heater positive with respect to cathode .	200 [▲] max. volts

** For definition of heater warm-up time and method of determining it, see sheet HEATER WARM-UP TIME MEASUREMENT at front of this Section.*

[▲] The dc component must not exceed 100 volts.