



5A24

5A24

FULL-WAVE VACUUM RECTIFIERGENERAL DATA**Electrical:**

Filament, Coated:

Voltage. 5 ac or dc volts
 Current. 2 amp

Mechanical:

Mounting Position. Vertical, or Horizontal with pins
 2 and 8 in horizontal plane

Maximum Overall Length 3-5/32"

Maximum Seated Length. 2-5/8"

Maximum Diameter 1-3/16"

Bulb T-9

Base Lock-in 8-Pin

Basing Designation for BOTTOM VIEW 5T

Pin 1-No


Connection

Pin 2-Filament

Pin 3-No

Connection

Pin 4-Plate



Pin 5-No

Connection

Pin 6-Plate

Pin 7-No

Connection

Pin 8-Filament

Plug -Base Shell

FULL-WAVE RECTIFIER**Maximum Ratings, Design-Center Values:**

PEAK INVERSE PLATE VOLTAGE 1400 max. volts
 PEAK PLATE CURRENT 375 max. ma
 DC OUTPUT CURRENT. 125 max. ma

Typical Operation:

	Capacitor- Input to Filter	Choke- Input to Filter	
AC Plate-to-Plate Supply			
Voltage (RMS).	700	1000	volts
Filter Input Capacitor	4	-	μf
Min. Total Effective Plate-Supply			
Impedance per Plate*.	50	-	ohms
Min. Filter Input Choke	-	5	henries
DC Output Current.	125	125	ma

* When the input capacitor of the filter exceeds 40 μf, it may be necessary to increase the plate-supply impedance in order to limit the peak current to the rated value.