#### Medium-Mu Triode— Sharp-Cutoff Pentode

# 9-PIN MINIATURE TYPE With Heater Having Controlled Warm-Up Time

The 5CG8	is	the	sai	ne as	the	: 6	CG	8 A	e 2	ссе	p t	Ĵ	or	the	following	items:
Heater,																
Voltag	ge	(AC	or	DC)	o 8	w	vt.	4	4	2	s	27		o &	4.7	volts
Currei	nt	s s	8	8 10	* 2		8	5	œ	a)·	ę.	æ	44	а «	$0.6 \pm 6\%$	amp

#### 5CL8A

#### Medium-Mu Triode— Sharp-Cutoff Tetrode

## 9-PIN MINIATURE TYPE With Heater Having Controlled Warm-Up Time

The 5CL8A is the same as the 6CL8A except for the following	items:
Heater, for Unipotential Cathodes:	
Voltage (AC or DC) 4.7	volts
Current 0.6 + 6%	amo

5CM8

#### High-Mu Triode— Sharp-Cutoff Pentode

### 9-PIN MINIATURE TYPE With Heater Having Controlled Warm-Up Time

- A	ine buno i	· 3 b	ne s	ume (	12 P	ne	UUI	10	83	cce	PL	J	OT	5 / L C	lorrominh	rems.
and out	Heater, f	or	Unij	pote	nti	a1	Car	tho	ode	9S:						
	Voltage	(A	Coi	r DC	).	я :	8 4	è	12	26	φ	9	a	ø ø	4.7	volts
	Current				_					_					$0.6 \pm 6\%$	amo