

5EA8

Medium-Mu Triode— Sharp-Cutoff Pentode

9-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 5EA8 is the same as the 6EA8 except for the following items:

Heater Characteristics and Ratings (Design-Maximum Values):

Current	0.600 ± 0.040	amp
Voltage (AC or DC) at heater amperes = 0.600	4.7	volts

5EU8

Medium-Mu Triode— Sharp-Cutoff Pentode

9-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 5EU8 is the same as the 6EU8 except for the following items:

Heater Characteristics and Ratings (Design-Center Values):

Current	0.600 ± 0.040	amp
Voltage (AC or DC) at heater amperes = 0.600	4.7	volts
Cathode Warm-Up Time ^a	35	sec

5EW6

Sharp-Cutoff Pentode

7-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 5EW6 is the same as the 6EW6 except for the following items:

Heater Characteristics and Ratings (Design-Maximum Values):

Current	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450	5.6	volts
Warm-up time (Average).	11	sec

^a The time required for the transconductance to reach 6500 μ mhos when the tube is operated from a cold start with dc plate volts = 100, grid volts = 0, and heater amperes = 0.560.

