

5GH8

Medium-Mu Triode— Sharp-Cutoff Pentode

9-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 5GH8 is the same as the 6GH8 except for the following items:

Heater Characteristics and Ratings (*Design-Maximum Values*):

Current	0.600 ± 0.040	amp
Voltage (AC or DC) at heater amperes = 0.600	4.7	volts

5GM6

Semiremote-Cutoff Pentode

7-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 5GM6 is the same as the 6GM6 except for the following items:

Heater Characteristics and Ratings (*Design-Maximum Values*):

Current	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450	5.6	volts
Warm-up time (Average).	11	sec

5GX6

Sharp-Cutoff Pentode With Two Independent Control Grids

7-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 5GX6 is the same as the 6GX6 except for the following items:

Heater Characteristics and Ratings (*Design-Maximum Values*):

Current	0.600 ± 0.040	amp
Voltage (AC or DC) at heater amperes = 0.600	4.7	volts



RADIO CORPORATION OF AMERICA
Electron Tube Division

Harrison, N. J.

DATA
5-62