



5V4-GA

5V4-GA

FULL-WAVE VACUUM RECTIFIER*For use in full-wave power supplies having high dc requirements***GENERAL DATA****Electrical:**

Heater, for Unipotential Cathode:


Voltage. 5 ac or dc volts
 Current. 2 amp

Mechanical:

Operating Position Any
 Maximum Overall Length 3-7/8"
 Maximum Seated Length. 3-5/16"
 Maximum Diameter 1-9/16"
 Bulb T12
 Base Medium-Shell Octal 5-Pin (JETEC No. B5-15), or
 Short Medium-Shell Octal 5-Pin
 with External Barriers, Style B,
 Arrangement 1 (JETEC No. B5-121)

Basing Designation for BOTTOM VIEW 5L

Pin 1 - No Connection
 Pin 2 - Heater
 Pin 4 - Plate of
 Unit No. 2



Pin 6 - Plate of
 Unit No. 1
 Pin 8 - Heater,
 Cathode

FULL-WAVE RECTIFIER**Maximum Ratings, Design-Center Values:**

PEAK INVERSE PLATE VOLTAGE 1400 max. volts
 AC PLATE-SUPPLY VOLTAGE PER PLATE (RMS):
 With capacitor-input filter. 375 max. volts
 With choke-input filter. 500 max. volts
 PEAK PLATE CURRENT PER PLATE 525 max. ma
 DC OUTPUT CURRENT. 175 max. ma

HOT-SWITCHING TRANSIENT PLATE CURRENT PER PLATE:

Even occasional hot-switching with capacitor-input circuits permits the flow of plate current having magnitudes which can adversely affect the life and reliability of tubes. If capacitor-input circuits are to be used, protect the circuits against the possibility of hot-switching and do not exceed a maximum peak current value per plate of 3.5 amperes during the initial cycles of the hot-switching transient. If hot-switching is required in operation, the use of choke-input circuits is recommended. Such circuits limit the hot-switching current to a value no higher than that of the peak plate current.



5V4-GA

FULL-WAVE VACUUM RECTIFIER

Typical Operation:*With capacitor input to filter*

AC Plate-to-Plate Supply Voltage (RMS) . .	750	volts
Filter-Input Capacitor*	10	μ f
Total Effective Plate-Supply Impedance		
Per Plate	100	ohms
DC Output Voltage at Input to Filter (Approx.) for dc output current of 175 ma.	410	volts

With choke input to filter

AC Plate-to-Plate Supply Voltage (RMS) . .	1000	volts
Filter-Input Choke	4	henries
DC Output Voltage at Input to Filter (Approx.) for dc output current of 175 ma.	410	volts


* Higher values of capacitance than indicated may be used, but the effective plate-supply impedance should be increased to prevent exceeding the maximum rating for peak plate current.



5V4-GA


FULL-WAVE VACUUM RECTIFIER

5V4-GA



CE-9549R1

AVERAGE PLATE CHARACTERISTIC EACH UNIT



5V4-GA



5V4-GA OPERATION CHARACTERISTICS FULL-WAVE RECTIFIER CIRCUIT

