



5Y4-G

5Y4-G
5Z3**FULL-WAVE HIGH-VACUUM RECTIFIER**

Filament	Coated	
Voltage	5.0	a-c volts
Current	2.0	amp.
Maximum Overall Length		4-5/8"
Maximum Diameter		1-13/16"
Bulb		ST-14
Base		Medium Shell Octal 8-Pin
Pin 1-No Connection		Pin 5-Plate #1
Pin 2-No Connection		Pin 6-No Connection
Pin 3-Plate #2		Pin 7-Filament
Pin 4-No Connection		Pin 8-Filament
Mounting Position		Vertical $\diamond$



BOTTOM VIEW (G-5Q)

$\diamond$ Horizontal operation permitted if pins 2 and 7 are in horizontal plane.


Maximum Ratings, Typical Operating Conditions, and Curves are the same as those for Type 5Y3-G.



5Z3

**FULL-WAVE HIGH-VACUUM RECTIFIER**

Filament	Coated	
Voltage	5.0	a-c volts
Current	3.0	amp.
Maximum Overall Length		5-3/8"
Maximum Diameter		2-1/16"
Bulb		ST-16
Base		Medium 4-Pin
Pin 1-Filament		Pin 3-Plate
Pin 2-Plate		Pin 4-Filament
Mounting Position		Vertical $\diamond$



BOTTOM VIEW (4C)

$\diamond$ Horizontal operation permitted if pins 1 and 4 are in horizontal plane.

Maximum Ratings, Typical Operating Conditions, and Curves are the same as those for Type 5U4-G.