



6AS7-G

6AS7-G

LOW-MU TWIN POWER TRIODE

GENERAL DATA

Electrical:

Heater, for Unipotential Cathodes:

Voltage. 6.3 ac or dc volts

Current. 2.5 amp

Direct Interelectrode Capacitances (Approx., each unit):^oGrid to plate. 10.5 μ fGrid to heater and cathode 6.8 μ fPlate to heater and cathode 2.3 μ fHeater to cathode. 11.0 μ fGrid of unit No.1 to grid of unit No.2 0.70 μ fPlate of unit No.1 to
plate of unit No.2. 1.65 μ fCharacteristics, Class A₁ Amplifier (Each unit):

Plate-Supply Voltage 135 volts

Cathode-Bias Resistor[■] 250 ohms

Amplification Factor 2

Plate Resistance (Approx.) 280 ohms

Transconductance 7000 μ mhos

Plate Current. 125 ma

Mechanical:

Mounting Position. Any

Maximum Overall Length 5-5/16"

Maximum Seated Length. 4-3/4"

Maximum Diameter 2-1/16"

Bulb ST-16

Base Medium-Shell Octal 8-Pin (JETEC No. B8-11)

Basing Designation for BOTTOM VIEW 8BD

Pin 1 - Grid of Unit No.2

Pin 2 - Plate of Unit No.2

Pin 3 - Cathode of Unit No.2


Pin 4 - Grid of Unit No.1

Pin 5 - Plate of Unit No.1

Pin 6 - Cathode of Unit No.1

Pin 7 - Heater

Pin 8 - Heater



DC AMPLIFIER

Values are for Each Unit

Maximum Ratings, Design-Center Values:

PLATE VOLTAGE. 250 max. volts

PLATE CURRENT. 125 max. ma

PLATE DISSIPATION. 13 max. watts

PEAK HEATER-CATHODE VOLTAGE:

Heater negative with respect to cathode. 300 max. volts

Heater positive with respect to cathode. 300 max. volts

^o Without external shield.[■] Operation with fixed bias is not recommended.

← Indicates a change.

MAY 1, 1955

TUBE DIVISION

DATA

RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY



6AS7-G

LOW-MU TWIN POWER TRIODE

Maximum Circuit Values (For maximum rated conditions):

Grid-Circuit Resistance:

For cathode-bias operation	1.0 max. megohm
For fixed-bias operation	Not recommended

BOOSTER SCANNING SERVICE

Values are for Each Unit

Maximum Ratings, Design-Center Values:

For operation in a 525-line, 30-frame system[□]

PEAK NEGATIVE-PULSE PLATE VOLTAGE [•]	1700 max.	volts
DC PLATE CURRENT	125 max.	ma
PLATE DISSIPATION.	13 max.	watts

PEAK HEATER-CATHODE VOLTAGE:

Heater negative with respect to cathode .	300 max.	volts
Heater positive with respect to cathode .	300 max.	volts

Maximum Circuit Values (For maximum rated conditions):

Grid-Circuit Resistance:

For cathode-bias operation	1.0 max. megohm
For fixed-bias operation	Not recommended

[□] As described in "Standards of Good Engineering Practice Concerning Television Broadcast Stations", Federal Communications Commission.


[•] The duration of the voltage pulse must not exceed 15 per cent of one horizontal scanning cycle. In a 525-line, 30-frame system, 15 per cent of one horizontal scanning cycle is 10 microseconds.



6AS7-G

AVERAGE PLATE CHARACTERISTICS EACH TRIODE UNIT

6AS7-G



NOV. 6, 1945

RCA VICTOR DIVISION
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

92CM-6618