

Dual Triode—Sharp-Cutoff Pentode

Dual Triode Has High-Mu & Medium-Mu Units

DUODECAR TYPE

Electrical:

Heater Characteristics and Ratings:

Voltage (AC or DC)	6.3 ± 0.6 volts
Current at 6.3 volts	1.050 amp
Maximum Heater Cathode Voltage:	
Heater negative with respect to cathode:	
Peak	200 volts
Heater positive with respect to cathode:	
Peak	200 volts
DC component	100 volts

Direct Interelectrode Capacitances: (Without external shield)

Triode Unit No.1

Grid to plate	1.9 pf
Input: G_{T1} to (K_{T1} , $K_{T2} + IS$, $K_p + G_{3p} + IS$, H)	3.0 pf
Output: P_{T1} to (K_{T1} , $K_{T2} + IS$, $K_p + G_{3p} + IS$, H)	2.2 pf

Triode Unit No.2

Grid to plate.	3.6 pf
Input: G_{T2} to ($K_{T2} + IS$, $K_p + G_{3p} + IS$, H)	2.4 pf
Output: P_{T2} to ($K_{T2} + IS$, $K_p + G_{3p} + IS$, H)	3.8 pf

Pentode Unit

Grid No.1 to plate	0.13 pf
Input: G_{1p} to ($K_{T2} + IS$, $K_p + G_{3p} + IS$, G_{2p} , H)	11.0 pf
Output: P_p to ($K_{T2} + IS$, $K_p + G_{3p} + IS$, G_{2p} , H)	4.6 pf
Pentode plate to plate of triode No.2.	0.045 max. pf
Plate of triode No.1 to plate of triode No.2.	0.075 max. pf

Characteristics, Class A₁ Amplifier:

	Triode Units No.1	No.2
Plate Supply Voltage	200	200 volts
Grid Voltage	-2	- volts
Cathode Resistor	-	220 ohms
Amplification Factor	68	41
Plate Resistance (Approx.)	12400	9400 ohms
Transconductance	5500	4400 μ mhos
Plate Current.	7	9.2 ma
Grid Voltage for plate $\mu a = 100$	-5.5	-6.5 volts

Pentode Unit


Plate Supply Voltage	35	135	volts
Grid-No.2 Supply Voltage	135	135	volts
Grid-No.1 Voltage.	0 ^a	-	volts
Cathode Resistor	-	100	ohms
Plate Resistance (Approx.)	-	45000	ohms
Transconductance	-	10400	μ mhos
Plate Current.	34 ^b	17	ma
Grid-No.2 Current.	13 ^b	4	ma
Grid-No.1 Voltage (Approx.) for plate $\mu a = 100$	-	-6	volts



6BD11

Mechanical:

- Operating Position Any
Types of Cathodes Coated Unipotential
Maximum Overall Length 2.375"
Seated Length 1.750" to 2.000"
Diameter 1.062" to 1.188"
Dimensional Outline (JEDEC 9-58) See *General Section*
Bulb T9
Base Small-Button Duodecar 12-Pin (JEDEC No.E12-70)
 Basing Designation for BOTTOM VIEW 12DP
- Pin 1-Heater
Pin 2-Pentode Plate
Pin 3-Grid of Triode Unit No.2
Pin 4-Plate of Triode Unit No.2
Pin 5-Cathode of Triode Unit No.1
Pin 6-Grid of Triode Unit No.1
Pin 7-Cathode of Triode Unit No.2,
 Internal Shield
Pin 8-Plate of Triode Unit No.1
Pin 9-Pentode Cathode, Pentode
 Grid No.3, Internal Shield
Pin 10-Pentode Grid No.2
Pin 11-Pentode Grid No.1
Pin 12-Heater



AMPLIFIER — Class A₁

Maximum Ratings, Design-Maximum Values:

	Triode Units No.1	No.2	
Plate Voltage	330	330	volts
Grid (Control-Grid) Voltage:			
Positive-bias value	0	0	volts
Plate Dissipation	1.5	2	watts

Pentode Unit

Plate Voltage	330	volts
Grid-No.2 (Screen-Grid) Supply Voltage	330	volts
Grid-No.2 Voltage	See <i>Grid-No.2 Input Rating Chart</i> at front of Receiving Tube Section	
Grid-No.1 (Control-Grid) Voltage:		
Positive-bias value	0	volts
Grid-No.2 Input:		
For grid-No.2 voltages up to 165 volts	1.1	watts
For grid-No.2 voltages between 165 and 330 volts	See <i>Grid-No.2 Input Rating Chart</i> at front of Receiving Tube Section	
Plate Dissipation	4	watts

Maximum Circuit Values: (Values are for Each Unit)

	Triode Units	Pentode Unit
Grid-No.1-Circuit Resistance:		
For fixed-bias operation	0.5	1 megohm
For cathode-bias operation	1	1 megohm

^a Applied for short interval (2 sec. max.) so as not to damage tube.
^b Value measured by recurrent waveform such that maximum ratings of tube are not exceeded.