

Beam Power Tube

7-PIN MINIATURE TYPE

GENERAL DATA

Electrical:

Heater, for Unipotential Cathode:

Voltage (AC or DC)	6.3 $\pm$ 10%	volts
Current at 6.3 volts.	1.2	amp


Direct Interelectrode Capacitances
(Approx.):^a

Grid No.1 to plate.	0.6	μ f
Grid No.1 to cathode & grid No.3, grid No.2, and heater	13	μ f
Plate to cathode & grid No.3, grid No.2, and heater	8.5	μ f

Mechanical:

Operating Position.	Any
Maximum Overall Length.	2-5/8"
Maximum Seated Length.	2-3/8"
Length, Base Seat to Bulb Top (Excluding tip)	2" $\pm$ 3/32"
Diameter.	0.650" to 0.750"
Dimensional Outline	See <i>General Section</i>
Bulb.	T5-1/2
Base.	Small-Button Miniature 7-Pin (JEDEC No.E7-1)
Basing Designation for BOTTOM VIEW.	7CV

Pin 1-Cathode,
Grid No.3
Pin 2-Grid No.1
Pin 3-Heater



Pin 4-Heater
Pin 5-Grid No.1
Pin 6-Grid No.2
Pin 7-Plate

AMPLIFIER — Class A₁

Maximum Ratings, Design-Maximum Values:

PLATE VOLTAGE	150 max.	volts
GRID-No.2 (SCREEN-GRID) VOLTAGE	130 max.	volts
GRID-No.1 (CONTROL-GRID) VOLTAGE:		
Positive-bias value	0 max.	volts
PLATE DISSIPATION	7 max.	watts
GRID-No.2 INPUT	1.4 max.	watts
PEAK HEATER-CATHODE VOLTAGE:		
Heater negative with respect to cathode.	200 max.	volts
Heater positive with respect to cathode.	200 ^b max.	volts
BULB TEMPERATURE (At hottest point on bulb surface).	220 max.	°C

← Indicates a change.



6CU5

Typical Operation and Characteristics:

Plate Voltage	120	volts
Grid-No.2 Voltage	110	volts
Grid-No.1 Voltage	-8	volts
Peak AF Grid-No.1 Voltage	8	volts
Zero-Signal Plate Current	49	ma
Max.-Signal Plate Current	50	ma
Zero-Signal Grid-No.2 Current	4	ma
Max.-Signal Grid-No.2 Current	8.5	ma
Plate Resistance (Approx.)	10000	ohms
Transconductance	7500	μ mhos
Load Resistance	2500	ohms
Total Harmonic Distortion	10	%
Max.-Signal Power Output	2.3	watts

Maximum Circuit Values:

Grid-No.1-Circuit Resistance:

For fixed-bias operation	0.1 max.	megohm
For cathode-bias operation	0.5 max.	megohm

^a Without external shield.

^b The dc component must not exceed 100 volts.






6CU5

AVERAGE CHARACTERISTICS

6CU5



TUBE DIVISION

92CM-8908RI


RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

6CU5



6CU5

OPERATION CHARACTERISTICS



TUBE DIVISION

RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

92CM-8918