



6DA4

6DA4

HALF-WAVE VACUUM RECTIFIER*For television damper service***GENERAL DATA****Electrical:**

Heater, for Unipotential Cathode:

Voltage (AC or DC) $6.3 \pm 10\%$ volts

Current 1.2 amp

Direct Interelectrode Capacitances
(Approx.):^oPlate to cathode and heater 6 μf Cathode to plate and heater 8 μf Heater to cathode 3 μf **Mechanical:**

Operating Position. Any

Maximum Overall Length. 3-5/16"

Maximum Seated Length 2-3/4"

Maximum Diameter. 1-9/32"

Dimensional Outline *See General Section*

Bulb. T9

Base. Intermediate-Shell Octal 5-Pin,

Arrangement 2 (JEDEC Group 1, No.B5-82),

Intermediate-Shell Octal 6-Pin,

Arrangement 1 (JEDEC Group 1, No.B6-8),

Short Intermediate-Shell Octal 5-Pin
with External Barriers, Arrangement 2

(JEDEC Group 1, No.B5-85), or


Short Intermediate-Shell Octal 6-Pin
with External Barriers, Arrangement 1

(JEDEC Group 1, No.B6-60)

Basing Designation for BOTTOM VIEW 4CG

Pin 1♦—Same as
Pin 2

Pin 2 — Internal

Connection—
Do Not Use●Pin 3—Cathode
Pin 5—Plate
Pin 7—Heater
Pin 8—Heater**DAMPER SERVICE****Maximum Ratings, Design-Maximum Values:***For operation in a 525-line, 30-frame system[□]*

PEAK INVERSE PLATE VOLTAGE* 4400 max. volts

PEAK PLATE CURRENT. 900 max. ma

DC PLATE CURRENT. 155 max. ma

PLATE DISSIPATION 5.5 max. watts

PEAK HEATER-CATHODE VOLTAGE:

Heater negative with respect to cathode . 4400[▲] max. voltsHeater positive with respect to cathode . 300[※] max. volts



6DA4

HALF-WAVE VACUUM RECTIFIER**Characteristics:**

Tube-Voltage Drop for plate

ma. = 250 22 volts

○ Without external shield.

◆ On the 5-pin bases, pin 1 as well as pins 4 and 6 is omitted.

● Socket terminals 1, 2, 4 and 6 should not be used as tie points.

□ As described in "Standards of Good Engineering Practice Concerning Television Broadcast Stations," Federal Communications Commission.

* This rating is applicable when the duty cycle of the voltage pulse does not exceed 15 per cent of one horizontal scanning cycle. In a 525-line, 30-frame system, 15 per cent of one horizontal scanning cycle is 10 microseconds.

▲ The dc component must not exceed 900 volts.

✱ The dc component must not exceed 100 volts.