



6DR7

6DR7

DUAL TRIODE

With High-Mu Unit and Low-Mu Unit

9-PIN MINIATURE TYPE

GENERAL DATA

Electrical:

Heater, for Unipotential Cathodes:

Voltage. 6.3 $\pm$ 10% ac or dc volts

Current. 0.9 amp

Direct Interelectrode Capacitances (Approx.):⁰

Unit No.1 Unit No.2

Grid to plate. 4.5 8.5 $\mu\mu\text{f}$ Grid to cathode and heater . . . 2.2 5.5 $\mu\mu\text{f}$ Plate to cathode and heater. . . 0.34 1 $\mu\mu\text{f}$ Characteristics, Class A₁ Amplifier:

Unit No.1 Unit No.2

Plate Voltage. 250 150 volts

Grid Voltage -3 -17.5 volts

Amplification Factor 68 6

Plate Resistance (Approx.) 40000 925 ohms

Transconductance 1600 6500 μmhos

Plate Current. 1.4 35 ma

Plate Current for plate volts = 60

and grid volts = 0 - 80 ma

Plate Current for grid volts = -24. - 10 ma

Grid Voltage (Approx.) for plate

 $\mu\text{a} = 10$ -5.5 - volts

Grid Voltage (Approx.) for plate

 $\mu\text{a} = 50$ - -44 volts

Mechanical:

Operating Position Any

Maximum Overall Length 2-5/8"

Maximum Seated Length. 2-3/8"

Length, Base Seat to Bulb Top (Excluding tip) . . . 2" $\pm$ 3/32"

Diameter 0.750" to 0.875"

Dimensional Outline. See General Section

Bulb T6-1/2


Base Small-Button Noval 9-Pin (JEDEC No.E9-1)

Basing Designation for BOTTOM VIEW 9HF

Pin 1-Plate of
Unit No.2Pin 2-Grid of
Unit No.2Pin 3-Grid of
Unit No.2

Pin 4-Heater

Pin 5-Heater

Pin 6-Plate of
Unit No.1Pin 7-Grid of
Unit No.1Pin 8-Cathode of
Unit No.1Pin 9-Cathode of
Unit No.2



DUAL TRIODE

With High-Mu Unit and Low-Mu Unit

VERTICAL-DEFLECTION OSCILLATOR

Values are for Unit No. 1

Maximum Ratings, Design-Maximum Values:

For operation in a 525-line, 30-frame system^o

DC PLATE VOLTAGE	330	max.	volts
PEAK NEGATIVE-PULSE GRID VOLTAGE	400	max.	volts
CATHODE CURRENT:			
Peak	70	max.	ma
Average.	20	max.	ma
PLATE DISSIPATION.	1	max.	watt
PEAK HEATER-CATHODE VOLTAGE:			
Heater negative with respect to cathode.	200	max.	volts
Heater positive with respect to cathode.	200 [■]	max.	volts

Maximum Circuit Values:

Grid-Circuit Resistance:

For grid-resistor-bias or cathode-bias operation	2.2	max.	megohms
--	-----	------	---------

VERTICAL-DEFLECTION AMPLIFIER

Values are for Unit No. 2

Maximum Ratings, Design-Maximum Values:

For operation in a 525-line, 30-frame system^o

DC PLATE VOLTAGE	275	max.	volts
PEAK POSITIVE-PULSE PLATE VOLTAGE [#] . . .	1500	max.	volts
PEAK NEGATIVE-PULSE GRID VOLTAGE	250	max.	volts
CATHODE CURRENT:			
Peak	175	max.	ma
Average.	50	max.	ma
PLATE DISSIPATION.	7	max.	watts
PEAK HEATER-CATHODE VOLTAGE:			
Heater negative with respect to cathode.	200	max.	volts
Heater positive with respect to cathode.	200 [■]	max.	volts

Maximum Circuit Values:

Grid-Circuit Resistance:

For grid-resistor-bias or cathode-bias operation	2.2	max.	megohms
--	-----	------	---------


^o Without external shield.

[•] As described in "Standards of Good Engineering Practice Concerning Television Broadcast Stations," Federal Communications Commission.

[#] This rating is applicable where the duration of the voltage pulse does not exceed 15 per cent of one vertical scanning cycle. In a 525-line, 30-frame system, 15 per cent of one vertical scanning cycle is 2.5 milliseconds.

[■] The dc component must not exceed 100 volts.

AVERAGE PLATE CHARACTERISTICS Unit No.1




92CM-9917



AVERAGE CHARACTERISTICS

Unit No.1




92CM-9915R1



6DR7

6DR7

AVERAGE PLATE CHARACTERISTICS UNIT No 2



6DR7



6DR7

AVERAGE CHARACTERISTICS

UNIT No 2

