

Medium-Mu Triode— Sharp-Cutoff Pentode

9-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

GENERAL DATA

Electrical:

Heater Characteristics and Ratings (*Design-Maximum Values*):

Voltage (AC or DC) 6.3^a 6.3 ± 0.6 volts

Current 0.450 ± 0.030 0.450^b amp

Warm-up time (Average) 11 — sec

Peak heater-cathode
voltage (Each unit):

Heater negative with
respect to cathode 200 max. volts

Heater positive with
respect to cathode 200^c max. volts

Direct Interelectrode Capacitances:

	<i>Without External Shield</i>	<i>With External Shield^d</i>	
Triode Unit:			
Grid to plate	1.8	1.8	μμf
Grid to cathode & pentode grid No.3, and heater . . .	3	3	μμf
Plate to cathode & pentode grid No.3, and heater . . .	1.3	1.9	μμf
Pentode Unit:			
Grid No.1 to plate	0.02 max.	0.01 max.	μμf
Grid No.1 to cathode & grid No.3, grid No.2, and heater	5	5	μμf
Plate to cathode & grid No.3, grid No.2, and heater	2.4	3.4	μμf
Heater to cathode & pentode grid No.3.	6	6 ^e	μμf

Characteristics, Class A₁ Amplifier:

	<i>Triode Unit</i>	<i>Pentode Unit</i>		
Plate Voltage	125	100	125	volts
Grid-No.2 Voltage	—	100	125	volts
Grid-No.1 Voltage	—1	0	—1	volts
Amplification Factor	43	—	—	
Plate Resistance (Approx.) . .	5700	—	180000	ohms
Transconductance	7500	7400	6000	μmhos
Plate Current	13	—	11	ma
Grid-No.2 Current	—	—	4	ma
Grid-No.1 Voltage (Approx.) for plate $\mu a = 30$	—6.5	—	—7.5	volts




6FG7

Mechanical:

Operating Position. Any
 Type of Cathode Coated Unipotential
 Maximum Overall Length. 2-3/16"
 Maximum Seated Length 1-15/16"
 Length, Base Seat to Bulb Top (Excluding tip) . 1-9/16" $\pm$ 3/32"
 Diameter. 0.750" to 0.875"
 Dimensional Outline See *General Section*
 Bulb. T6-1/2
 Base. Small-Button Noval 9-Pin (JEDEC No.E9-1)
 Basing Designation for BOTTOM VIEW. 9GF

Pin 1-Triode Grid
 Pin 2-Triode Plate
 Pin 3-Cathode
 Pin 4-Heater
 Pin 5-Heater
 Pin 6-Pentode Plate



Pin 7-Pentode
 Grid No.2
 Pin 8-Cathode,
 Pentode
 Grid No.3
 Pin 9-Pentode
 Grid No.1

AMPLIFIER — Class A₁

Maximum Ratings, Design-Maximum Values:

	Triode Unit	Pentode Unit	
PLATE VOLTAGE	330 max.	330 max.	volts
GRID-No.2 (SCREEN-GRID) SUPPLY VOLTAGE.	-	330 max.	volts
GRID-No.2 VOLTAGE	-	See <i>Grid-No.2 Input</i>	
<i>Rating Chart</i> at front of Receiving Tube Section			
GRID-No.1 (CONTROL-GRID) VOLTAGE:			
Positive-bias value	0 max.	0 max.	volts
GRID-No.2 INPUT:			
For grid-No.2 voltages up to 165 volts	-	0.55 max.	watt
For grid-No.2 voltages between 165 and 330 volts	-	See <i>Grid-No.2 Input</i>	
<i>Rating Chart</i> at front of Receiving Tube Section			
PLATE DISSIPATION	2.5 max.	3 max.	watts

^a At heater amperes = 0.450.

^b At heater volts = 6.3.

^c The dc component must not exceed 100 volts.

^d With external shield JEDEC No.315 connected to cathode except as noted.

^e With external shield JEDEC No.315 connected to ground.

