



6SN7-GTA

6SN7-GTA

MEDIUM-MU TWIN TRIODE

GENERAL DATA

Electrical:

Heater, for Unipotential Cathodes:

Voltage 6.3 ac or dc volts
 Current 0.6 amp

Direct Interelectrode Capacitances (With no external shield):

	Unit No. 1	Unit No. 2	
Grid to plate	4	3.8	μmf
Grid to cathode and heater . .	2.2	2.6	μmf
Plate to cathode and heater . .	0.7	0.7	μmf


Characteristics, Class A₁ Amplifier (Each Unit):

Plate Voltage	90	250	volts
Grid Voltage	0	-8	volts
Amplification Factor	20	20	volts
Plate Resistance (Approx.) . . .	6700	7700	ohms
Transconductance	3000	2600	μmhos
Plate Current	10	9	ma
Plate Current for grid voltage of -12.5 volts	-	1.3	ma
Grid Voltage (Approx.) for plate current of 10 μamp	-7	-18	volts

Mechanical:

Mounting Position Any
 Maximum Overall Length 3-5/16"
 Maximum Seated Length 2-3/4"
 Maximum Diameter 1-9/32"
 Bulb T-9
 Base Short Intermediate-Shell Octal 8-Pin
 with External Barriers (JETEC No. B8-58)
 Basing Designation for BOTTOM VIEW 8BD

Pin 1 - Grid of
Unit No. 2
 Pin 2 - Plate of
Unit No. 2
 Pin 3 - Cathode of
Unit No. 2
 Pin 4 - Grid of
Unit No. 1



Pin 5 - Plate of
Unit No. 1
 Pin 6 - Cathode of
Unit No. 1
 Pin 7 - Heater
 Pin 8 - Heater

AMPLIFIER - Class A₁

Values are for Each Unit

Maximum Ratings, Design-Center Values:

PLATE VOLTAGE 450 max. volts
 CATHODE CURRENT 20 max. ma



6SN7-GTA

MEDIUM-MU TWIN TRIODE

PLATE DISSIPATION:

Either plate	5	max.	watts
Both plates (Both units operating) . . .	7.5	max.	watts

PEAK HEATER-CATHODE VOLTAGE:

Heater negative with respect to cathode	200	max.	volts
Heater positive with respect to cathode	200 [▲]	max.	volts

Maximum Circuit Values:

Grid-Circuit Resistance:

For fixed-bias operation	1	max.	megohm
------------------------------------	---	------	--------

Typical Operation as Resistance-Coupled Amplifier:

See RESISTANCE-COUPLED AMPLIFIER CHART No.29
at front of this Section

HORIZONTAL DEFLECTION OSCILLATOR

Values are for Each Unit

Maximum Ratings, Design-Center Values:

For operation in a 525-line, 30-frame system[□]

DC PLATE VOLTAGE	450	max.	volts
PEAK NEGATIVE-PULSE GRID VOLTAGE [●]	600	max.	volts
CATHODE CURRENT:			
Peak	300	max.	ma
Average	20	max.	ma

PLATE DISSIPATION:

Either plate	5	max.	watts
Both plates (Both units operating) . . .	7.5	max.	watts

PEAK HEATER-CATHODE VOLTAGE:

Heater negative with respect to cathode	200	max.	volts
Heater positive with respect to cathode	200 [▲]	max.	volts

Maximum Circuit Values:

Grid-Circuit Resistance:

For fixed-bias, grid-resistor bias, or cathode-bias operation	2.2	max.	megohms
--	-----	------	---------

VERTICAL DEFLECTION OSCILLATOR

Values are for Each Unit

Maximum Ratings, Design-Center Values:

For operation in a 525-line, 30-frame system[□]

DC PLATE VOLTAGE	450	max.	volts
PEAK NEGATIVE-PULSE GRID VOLTAGE [#]	400	max.	volts
CATHODE CURRENT:			
Peak	70	max.	ma
Average	20	max.	ma

[▲], [□], [●], [#]: See next page.



6SN7-GTA

6SN7-GTA

MEDIUM-MU TWIN TRIODE

PLATE DISSIPATION:

Either plate	5	max.	watts
Both plates (Both units operating) . . .	7.5	max.	watts

PEAK HEATER-CATHODE VOLTAGE:

Heater negative with respect to cathode	200	max.	volts
Heater positive with respect to cathode	200 [▲]	max.	volts

Maximum Circuit Values:

Grid-Circuit Resistance:

For fixed-bias, grid-resistor bias, or cathode-bias operation	2.2	max.	megohms
--	-----	------	---------

VERTICAL DEFLECTION AMPLIFIER

Values are for Each Unit

Maximum Ratings, Design-Center Values Except as Noted:

For operation in a 525-line, 30-frame system[□]

DC PLATE VOLTAGE	450	max.	volts
----------------------------	-----	------	-------

PEAK POSITIVE-PULSE PLATE VOLTAGE [#] (Absolute Maximum) . . .	1500 [■]	max.	volts
--	-------------------	------	-------

PEAK NEGATIVE-PULSE GRID VOLTAGE	250	max.	volts
--	-----	------	-------

CATHODE CURRENT:

Peak	70	max.	ma
Average	20	max.	ma

PLATE DISSIPATION:

Either plate	5	max.	watts
Both plates (Both units operating) . . .	7.5	max.	watts

PEAK HEATER-CATHODE VOLTAGE:

Heater negative with respect to cathode	200	max.	volts
Heater positive with respect to cathode	200 [▲]	max.	volts

Maximum Circuit Values:

Grid-Circuit Resistance:

For cathode-bias operation	2.2	max.	megohms
--------------------------------------	-----	------	---------


[▲] The dc component must not exceed 100 volts.[□] As described in "Standards of Good Engineering Practice Concerning Television Broadcast Stations", Federal Communications Commission.[♣] This rating is applicable where the duration of the voltage pulse does not exceed 15 per cent of one horizontal scanning cycle. In a 525-line, 30-frame system, 15 per cent of one horizontal scanning cycle is 10 microseconds.[#] This rating is applicable where the duration of the voltage pulse does not exceed 15 per cent of one vertical scanning cycle. In a 525-line, 30-frame system, 15 per cent of one vertical scanning cycle is 2.5 milliseconds.[■] under no circumstances should this absolute value be exceeded.

6SN7-GTA



6SN7-GTA

AVERAGE PLATE CHARACTERISTICS FOR EACH UNIT



APRIL. 28, 1954

TUBE DIVISION

92CM-8322

RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY



6SN7-GTA

6SN7-GTA

AVERAGE CHARACTERISTICS FOR EACH UNIT

