

8CS7

Medium-Mu Dual Triode

With Dissimilar Units

9-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 8CS7 is the same as the 6CS7 except for the following items:

Heater Characteristics and Ratings (*Design-Center Values*):

Current	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450	8.4	volts
Warm-up time (Average).	11	sec

8CX8

Medium-Mu Triode— Sharp-Cutoff Pentode

9-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 8CX8 is the same as the 6CX8 except for the following items:

Heater Characteristics and Ratings (*Design-Maximum Values*):

Current	0.600 ± 0.040	amp
Voltage (AC or DC) at heater amperes = 0.600	8.0	volts
Warm-up time (Average).	11	sec

8EB8

High-Mu Triode— Sharp-Cutoff Pentode

9-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 8EB8 is the same as the 6EB8 except for the following items:

Heater Characteristics and Ratings (*Design-Maximum Values*):

Current	0.600 ± 0.040	amp
Voltage (AC or DC) at heater amperes = 0.600	8.0	volts
Warm-up time (Average).	11	sec

