

8JU8A

Quadruple Diode

The 8JU8A is the same as the 6JU8A except for the following items:

Heater Characteristics and Ratings

Current.	0.450 ± 0.030	A
Voltage (AC or DC) at 0.450 A.	8.4	V
Warm-up time (Average)	11	s

8JV8

High-Mu Triode—Sharp-Cutoff Pentode

The 8JV8 is the same as the 6JV8 except for the following items:

Heater Characteristics and Ratings

Current.	0.450 ± 0.030	A
Voltage (AC or DC) at 0.450 A.	8.5	V
Warm-up time (Average)	11	s

8KA8

High-Mu Triode—Sharp-Cutoff Pentode

Pentode Unit Has Two Independent Control Grids

The 8KA8 is the same as the 6KA8 except for the following items:

Heater Characteristics and Ratings

Current.	0.450 ± 0.030	A
Voltage (AC or DC) at 0.450 A.	8.4	V
Warm-up time (Average)	11	s

8LC8

High-Mu Triode—Sharp-Cutoff Pentode

The 8LC8 is the same as the 6LC8 except for the following items:

Heater Characteristics and Ratings

Current.	0.450 ± 0.030	A
Voltage (AC or DC) at 0.450 A.	8.4	V
Warm-up time (Average)	11	s