

Pentagrid Converter

7-PIN MINIATURE TYPE

For Automobile Radio Receivers Operating
Directly from 6-Cell Storage Batteries

GENERAL DATA

Electrical:

Heater, for Unipotential Cathode:

Voltage range (DC). 10 to 15.9 volts

For longest life, it is recommended that the heater be operated within the voltage range of 11 to 14 volts.

Current (Approx.) at 12.6 volts 0.15 amp

Direct Interelectrode Capacitances:

	Without External Shield	With External Shield ^a	
Grid No.3 to all other electrodes (RF input)	7	7	μf
Plate to all other electrodes (Mixer output) . .	7	12	μf
Grid No.1 to cathode & grid No.5, plate, grid No.3, and heater (Oscillator input) .	3.2	3.2	μf
Grid No.3 to plate.	0.3 max.	0.26 max.	μf
Grid No.3 to grid No.1.	0.15 max.	0.15 max.	μf
Grid No.1 to grid No.2 & grid No.4	2.2	2.2	μf
Grid No.2 & grid No.4 to all other electrodes except grid No.1 (Oscillator output). . .	11	11	μf

Mechanical:

Operating Position. Any

Maximum Overall Length. 2-1/8"

Maximum Seated Length 1-7/8"

Length, Base Seat to Bulb Top (Excluding tip). . . 1-1/2" $\pm$ 3/32"

Diameter. 0.650" to 0.750"


Dimensional Outline See *General Section*

Bulb. T5-1/2

Base. Small-Button Miniature 7-Pin (JEDEC No.E7-1)

Basing Designation for BOTTOM VIEW. 7CH

Pin 1—Grid No.1
Pin 2—Cathode,
Grid No.5
Pin 3—Heater
Pin 4—Heater



Pin 5—Plate
Pin 6—Grid No.2,
Grid No.4
Pin 7—Grid No.3

← Indicates a change.



12AD6

CONVERTER

Maximum Ratings, Design-Maximum Values:

PLATE VOLTAGE.	16 max.	volts
GRID-No.3 (CONTROL-GRID) VOLTAGE:		
Negative-bias value.	16 max.	volts
Positive-bias value.	0 max.	volts
GRIDS-No.2 & No.4 (SCREEN-GRID) SUPPLY VOLTAGE.	16 max.	volts
GRIDS-No.2 & No.4 VOLTAGE.	16 max.	volts
TOTAL CATHODE CURRENT.	20 max.	ma
PEAK HEATER-CATHODE VOLTAGE:		
Heater negative with respect to cathode. . .	16 max.	volts
Heater positive with respect to cathode. . .	16 max.	volts

Typical Operation and Characteristics:

With separate excitation^b and with heater voltage of 12.6 volts

Plate Voltage.	10.6	12.6	14.6	volts
Grids-No.2 & No.4 Voltage. . . .	10.6	12.6	14.6	volts
Grid-No.3 Supply Voltage	0	0	0	volts
Grid-No.3 Resistor	2.2	2.2	2.2	megohms
Peak-to-Peak Grid-No.1 (Oscillator-Grid) Voltage. . .	4.5	4.5	4.5	volts
Grid-No.1 Resistor	33000	33000	33000	ohms
Plate Resistance (Approx.) . . .	0.5	0.4	0.2	megohm
Conversion Transconductance. . .	—	320	—	μ hos
Grid-No.3 Voltage (Approx.) for conversion transconductance (μ hos) =				
5.	—	-3	—	volts
0.5.	—	-4	—	volts
Plate Current.	—	0.35	—	ma
Grid-No.1 Current.	—	0.06	—	ma
Total Cathode Current.	—	1.6	—	ma

Oscillator Characteristics (Not Oscillating):

*With grids No.2 & No.4 connected to plate
and with heater voltage of 12.6 volts*

Plate and Grids-No.2 & No.4 Voltage.	12.6	volts
Grid-No.3 Voltage.	0	volts
Grid-No.1 Voltage.	0	volts
Amplification Factor between grid No.1 and grids No.2 & No.4 connected to plate	9.4	
Transconductance between grid No.1 and grids No.2 & No.4 connected to plate	3600	μ hos
Cathode Current.	4.5	ma
Grid-No.1 Voltage (Approx.) for plate μ a = 10 .	-3.7	volts

Maximum Circuit Values:

Grid-No.3-Circuit Resistance	10 max.	megohms
--	---------	---------

^a With external shield JEDEC No.316 connected to cathode & grid No.5.

^b The characteristics shown with separate excitation correspond very closely with those obtained in a self-excited oscillator circuit operating with zero bias.

➔ Indicates a change.

