



12AH7-GT

12AH7-GT

MEDIUM-MU TWIN TRIODE

GENERAL DATA

Electrical:

Heater, for Unipotential Cathodes:

Voltage. 12.6 ac or dc volts

Current. 0.15 amp

Direct Interelectrode Capacitances (Approx.):⁰

	Unit No.1	Unit No.2	
Grid to plate.	3	2.2	μf
Grid to cathode and heater	2.8	3.2	μf
Plate to cathode and heater	2.6	3	μf
Plate of unit No.1 to plate of unit No.2	0.4		μf
Grid of unit No.1 to grid of unit No.2.	0.06		μf


Characteristics, Class A₁ Amplifier (Each unit):

Plate Voltage.	100	180	volts
Grid Voltage	-3.6	-6.5	volts
Amplification Factor	16	16	
Plate Resistance (Approx.)	10300	8400	ohms
Transconductance	1550	1900	μmhos
Plate Current.	3.7	7.6	ma
Grid Voltage (Approx.) for plate current of 10 μamp	-8.5	-16	volts

Mechanical:

Mounting Position.	Any
Maximum Overall Length	3-1/16"
Maximum Seated Length.	2-1/2"
Maximum Diameter	1-9/32"
Dimensional Outline.	See General Section
Bulb	T-9
Base	Intermediate-Shell Octal 8-Pin (JETEC No. B8-6)
Basing Designation for BOTTOM VIEW	8BE

Pin 1 - Grid of
Unit No.2
Pin 2 - Cathode of
Unit No.2
Pin 3 - Plate of
Unit No.2
Pin 4 - Cathode of
Unit No.1



Pin 5 - Grid of
Unit No.1
Pin 6 - Plate of
Unit No.1
Pin 7 - Heater
Pin 8 - Heater

⁰ With external shield JETEC No. 308 connected to cathode of unit under test.

← Indicates a change.

12AH7-GT



12AH7-GT

MEDIUM-MU TWIN TRIODE

AMPLIFIER - Class A₁

Values are for Each Unit

Maximum Ratings, Design-Center Values:

PLATE VOLTAGE.	180 max.	volts
PLATE-SUPPLY VOLTAGE	300 max.	volts
PLATE DISSIPATION.	1.5 max.	watts
→ PEAK HEATER-CATHODE VOLTAGE:		
Heater negative with respect to cathode.	200 max.	volts
Heater positive with respect to cathode.	200 [▲] max.	volts

[▲] The dc component must not exceed 100 volts.

→ Indicates a change.