

Half-Wave Vacuum Rectifier

DUODECAR TYPE

With Heater Having Controlled Warm-Up Time

The 12AX3 is the same as the 6AX3 except for the following items:

Heater Characteristics and Ratings (Design-Maximum Values):

Voltage (AC or DC)	12.6 ^a	12.6 ± 1.2	volts
Current	0.600 ± 0.040	0.600 ^b	amp
Warm-up time (Average) . . .	11	—	sec

12AX4GTA

Half-Wave Vacuum Rectifier

For Damper Service in TV Equipment With
Heater Having Controlled Warm-Up Time

The 12AX4GTA is the same as the 6AX4GT except for the following items:

Heater Characteristics and Ratings (Design-Maximum Values):

Voltage (AC or DC)	12.6 ^a	12.6 ± 1.2	volts
Current	0.600 ± 0.040	0.600 ^b	amp
Warm-up time (Average) . . .	11	—	sec

12AX4GTB

Half-Wave Vacuum Rectifier

For Damper Service in TV Equipment With
Heater Having Controlled Warm-Up Time

The 12AX4GTB is the same as the 6AX4GTB except for the following items:

Heater Characteristics and Ratings (Design-Maximum Values):

Voltage (AC or DC)	12.6 ^a	12.6 ± 1.2	volts
Current	0.600 ± 0.040	0.600 ^b	amp
Warm-up time (Average) . . .	11	—	sec

^a At heater amperes = 0.600.

^b At heater volts = 12.6.

