

12AX7-A

High-Mu Twin Triode

9-PIN MINIATURE TYPE

For High-Fidelity Audio-Amplifier Applications Critical as to Noise and Hum

GENERAL DATA

Electrical:

Heater, for Unipotential Cathodes:

Heater arrangement	Series	Parallel	
Voltage (AC or DC)	12.6	$6.3 \pm 10\%$	volts
Current	$0.15 \pm 6\%$	0.3	amp

Direct Interelectrode Capacitances (Approx.):[▲]

	Unit No. 1	Unit No. 2	
Grid to plate	1.7	1.7	μmf
Grid to cathode and heater . .	1.6	1.6	μmf
Plate to cathode and heater . .	0.46	0.34	μmf

Equivalent Noise and Hum Voltage

(Referenced to Grid, Each Unit):

Average Value (RMS)	1.8	μvolts
Measured in "true rms" units under the following conditions: Heater volts (AC) = 6.3; center-tap of heater transformer connected to ground; plate supply volts (DC) = 250; plate load resistor (megohms) = 0.1; cathode resistor (ohms) = 2700; cathode bypass capacitor (μf) = 100; grid resistor (ohms) = 0; amplifier frequency range 25 to 10000 cps.		

Characteristics, Class A₁ Amplifier (Each Unit):

Plate Voltage	100	250	volts
Grid Voltage	-1	-2	volts
Amplification Factor	100	100	
Plate Resistance (Approx.)	80000	62500	ohms
Transconductance	1250	1600	μmhos
Plate Current	0.5	1.2	ma

Mechanical:

Operating Position	Any
Maximum Overall Length	2-3/16"
Maximum Seated Length	1-15/16"
Length, Base Seat to Bulb Top (Excluding tip).	1-9/16" $\pm$ 3/32"
Diameter	0.750" to 0.875"
Dimensional Outline	See General Section
Bulb	T6-1/2
Base	Small-Button Noval 9-Pin (JEDEC No. E9-1)



12AX7-A

Basing Designation for BOTTOM VIEW 9A


Pin 1—Plate of
Unit No.2

Pin 2—Grid of
Unit No.2

Pin 3—Cathode of
Unit No.2

Pins 4 & 9—Heater of
Unit No.2

Pins 5 & 9—Heater of
Unit No.1



Pin 6—Plate of
Unit No.1

Pin 7—Grid of
Unit No.1

Pin 8—Cathode of
Unit No.1

Pin 9—Heater Tap

AMPLIFIER — CLASS A₁

Values are for Each Unit

Maximum Ratings, Design-Maximum Values:

PLATE VOLTAGE.	330	max.	volts
GRID VOLTAGE:			
Negative-bias value.	55	max.	volts
Positive-bias value.	0	max.	volts
PLATE DISSIPATION.	1.2	max.	watts
PEAK HEATER-CATHODE VOLTAGE:			
Heater negative with respect to cathode.	200	max.	volts
Heater positive with respect to cathode.	200	max.	volts

Typical Operation as Resistance-Coupled Amplifier:


See *RESISTANCE-COUPLED-AMPLIFIER CHART No. 25*
at front of this Section

▲ Without external shield.

● The dc component must not exceed 100 volts.

12AX7-A

AVERAGE PLATE CHARACTERISTICS Each Unit



92CM-6879




RADIO CORPORATION OF AMERICA
Electron Tube Division
Harrison, N. J.

DATA 2
10-60

12AX7-A

AVERAGE CHARACTERISTICS Each Unit



92CM-6880

