



12B8-GT

TRIODE-PENTODE

12B8-GT

Heater ■	Coated Unipotential Cathodes	
Voltage	12.6	a-c or d-c volts
Current	0.3	amp.

Direct Interelectrode Capacitances:^o*Triode Unit:*

Grid to Plate	2.3	μf
Grid to Cathode	5.0	μf
Plate to Cathode	6.3	μf

Pentode Unit:

Grid to Plate	0.015	μf
Input	5.2	μf
Output	9.6	μf
Pentode Grid to Triode Grid	0.002	μf
Pentode Plate to Triode Grid	0.078	μf
Pentode Grid to Triode Plate	0.003	μf

Maximum Overall Length 3-9/16"

Maximum Seated Height 3"


Maximum Diameter 1-5/16"

Bulb T-9

Cap Skirted Miniature

Base Intermediate Shell Octal 8-Pin

Pin 1 - Pentode Cathode	Pin 6 - Triode Cathode
Pin 2 - Heater	Pin 7 - Heater
Pin 3 - Pentode Plate	Pin 8 - Triode Grid
Pin 4 - Pentode Screen	Cap - Pentode Grid
Pin 5 - Triode Plate	



BOTTOM VIEW (8T)

TRIODE UNIT*Typical Operation and Characteristics:*

Plate	90	volts
Grid	0	volts
Amp. Fact.	90	
Plate Res.	37000	ohms
Transcond.	2400	μmhos
Grid Bias (approx.) for		
Plate-Cur. Cut-Off	-2.5	volts
Plate Current	2.8	ma.

PENTODE UNIT*Typical Operation and Characteristics:*

Plate	90	volts
Screen	90	volts
Grid	-3	volts
Plate Res.	200000	ohms
Transcond.	1800	μmhos
Grid Bias for		
Transcond. of 2 μmhos	-42.5	volts
Plate Cur.	7.0	ma.
Screen Cur.	2.0	ma.

■ In circuits where the cathode is not directly connected to the heater, the potential difference between heater and cathode should be kept as low as possible.

o Values are approximate.