

# 12BQ6GTB/12CU6

## Beam Power Tube

*The 12BQ6GTB/12CU6 is the same as the 6BQ6GTB/6CU6 except for the following items:*

### Heater Characteristics and Ratings:

|                                                           |               |       |
|-----------------------------------------------------------|---------------|-------|
| Current. . . . .                                          | 0.600 ± 0.040 | amp   |
| Voltage (AC or DC) at heater<br>amperes = 0.600 . . . . . | 12.6          | volts |
| Warm-up time (Average) . . . . .                          | 11            | sec   |

# 12BS3

## Half-Wave Vacuum Rectifier

### NOVAR TYPE

#### For TV Damper Service

*The 12BS3 is the same as the 6BS3 except for the following items:*

### Heater Characteristics and Ratings:

|                                                           |               |       |
|-----------------------------------------------------------|---------------|-------|
| Current. . . . .                                          | 0.600 ± 0.040 | amp   |
| Voltage (AC or DC) at heater<br>amperes = 0.600 . . . . . | 12.6          | volts |
| Warm-up time (Average) . . . . .                          | 11            | sec   |

# 12BS3A

## Half-Wave Vacuum Rectifier

### NOVAR TYPE

#### For TV Damper Service

*The 12BS3A is the same as the 6BS3A except for the following items:*

### Heater Characteristics and Ratings:

|                                                           |               |       |
|-----------------------------------------------------------|---------------|-------|
| Current. . . . .                                          | 0.600 ± 0.040 | amp   |
| Voltage (AC or DC) at heater<br>amperes = 0.600 . . . . . | 12.6          | volts |
| Warm-up time (Average) . . . . .                          | 11            | sec   |

