



12CR6

12CR6

DIODE-REMOTE-CUTOFF PENTODE

7-PIN MINIATURE TYPE

GENERAL DATA

Electrical:

Heater, for Unipotential Cathode:

Voltage. 12.6 ac or dc volts
 Current. 0.15 amp


Mechanical:

Mounting Position. Any
 Maximum Overall Length. 2-1/8"
 Maximum Seated Length. 1-7/8"
 Length, Base Seat to Bulb Top (Excluding tip). . 1-1/2" $\pm$ 3/32"
 Maximum Diameter. 3/4"
 Dimensional Outline. See General Section
 Bulb T-5-1/2
 Base Small-Button Miniature 7-Pin (JETEC No. E7-1)
 Basing Designation for BOTTOM VIEW 7EA

Pin 1-Cathode,
 Pentode
 Grid No. 3

Pin 2-Diode
 Plate

Pin 3-Heater
 Pin 4-Heater



Pin 5-Pentode
 Plate

Pin 6-Pentode
 Grid No. 2

Pin 7-Pentode
 Grid No. 1

PENTODE UNIT - Class A₁ Amplifier

Maximum Ratings, Design-Center Values:

PLATE VOLTAGE. 300 max. volts
 GRID-No. 2 (SCREEN-GRID) SUPPLY VOLTAGE. . . 300 max. volts
 GRID-No. 2 VOLTAGE. See Grid-No. 2 Input Rating Chart
 at front of Receiving Tube Section

GRID-No. 1 (CONTROL-GRID) VOLTAGE:

Positive bias value. 0 max. volts

PLATE DISSIPATION. 2.5 max. watts

GRID-No. 2 INPUT:

For grid-No. 2 voltages up to 150 volts. 0.3 max. watt

For grid-No. 2 voltages between 150

and 300 volts. See Grid-No. 2 Input Rating Chart
 at front of Receiving Tube Section

PEAK HEATER-CATHODE VOLTAGE:

Heater negative with respect to cathode. 100 max. volts

Heater positive with respect to cathode. 100 max. volts

Characteristics:

Plate Voltage. 250 volts

Grid-No. 2 Voltage. 100 volts

Grid-No. 1 Voltage. -2 volts

Plate Resistance (Approx.) 0.8 megohm

Transconductance 2200 μ mhos

12CR6



12CR6

DIODE-REMOTE-CUTOFF PENTODE

Plate Current.	9.6	ma
Grid-No.2 Current.	2.6	ma
Grid-No.1 Voltage (Approx.) for transconductance of 10 μ mhos	-32	volts

Maximum Circuit Values:


Grid-No.1-Circuit Resistance:		
For cathode-bias operation	1.0 max.	megohm
For fixed-bias operation	0.25 max.	megohm

DIODE UNIT

Maximum Ratings, Design-Center Values:

PLATE CURRENT.	1.0 max.	ma
------------------------	----------	----

AVERAGE PLATE CHARACTERISTIC DIODE UNIT





12CR6

12CR6

AVERAGE PLATE CHARACTERISTICS PENTODE UNIT

$E_f = 12.6$ VOLTS
GRID-Nº2 VOLTS=100




PLATE MILLIAMPERES

PLATE VOLTS

TUBE DIVISION

RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY


92CM-9006

12CR6



12CR6

AVERAGE CHARACTERISTICS PENTODE UNIT



TUBE DIVISION

RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

92CM-9004