



12K7-GT

## REMOTE-CUTOFF PENTODE

12K7-GT  
12Q7-GT

Heater, for Unipotential Cathode:

Voltage . . . . . 12.6 . . . . . ac or dc volts

Current . . . . . 0.15 . . . . . amp

*The 12K7-GT is the same as the 6K7-GT except for heater rating.*

12K8

## TRIODE-HEXODE CONVERTER

Heater, for Unipotential Cathode:

Voltage . . . . . 12.6 . . . . . ac or dc volts

Current . . . . . 0.15 . . . . . amp

*The 12K8 is the same as the 6K8 except for heater rating.*

12L6-GT

## BEAM POWER TUBE

*Intended for use in equipment having  
series heater-string arrangement*

*The 12L6-GT is the same as the 25L6-GT except for the following items:*

Heater, for Unipotential Cathode:

Voltage . . . . . 12.6 . . . . . ac or dc volts

Current . . . . . 0.6 . . . . . amp

Warm-up time (Average). . . 11 . . . . . sec

*For definition of heater warm-up time and method of determining it, see sheet HEATER WARM-UP TIME MEASUREMENT at front of this Section.*

PEAK HEATER-CATHODE VOLTAGE:

Heater negative with respect to cathode . . 300 max. volts

Heater positive with respect to cathode . . 200<sup>▲</sup>max. volts

<sup>▲</sup> The dc component must not exceed 100 volts.

12Q7-GT

## TWIN DIODE—HIGH-MU TRIODE

Heater, for Unipotential Cathode:

Voltage . . . . . 12.6 . . . . . ac or dc volts

Current . . . . . 0.15 . . . . . amp

*The 12Q7-GT is the same as the 6Q7-GT except for heater rating.*