

12SJ7
TO
12SR7



12SJ7, 12SJ7-GT

TRIPLE-GRID DETECTOR AMPLIFIER

Heater ■	Coated Unipotential Cathode	
Voltage	12.6	a-c or d-c volts
Current	0.15	amp.

The 12SJ7 and 12SJ7-GT are the same as the 6SJ7 and 6SJ7-GT respectively except for heater rating.

12SK7, 12SK7-GT/G

TRIPLE-GRID SUPER-CONTROL AMPLIFIER

Heater ■	Coated Unipotential Cathode	
Voltage	12.6	a-c or d-c volts
Current	0.15	amp.

The 12SK7 and 12SK7-GT/G are the same as the 6SK7 and 6SK7-GT/G respectively except for heater rating.

12SL7-GT

TWIN-TRIODE AMPLIFIER

Heater ■	Coated Unipotential Cathodes	
Voltage	12.6	a-c or d-c volts
Current	0.15	amp.

The 12SL7-GT is the same as the 6SL7-GT except for heater rating.

12SN7-GT

TWIN-TRIODE AMPLIFIER

Heater ■	Coated Unipotential Cathodes	
Voltage	12.6	a-c or d-c volts
Current	0.30	amp.

The 12SN7-GT is the same as the 6SN7-GT except for heater rating.

12SQ7, 12SQ7-GT/G

DUPLEX-DIODE HIGH-MU TRIODE

Heater ■	Coated Unipotential Cathode	
Voltage	12.6	a-c or d-c volts
Current	0.15	amp.

The 12SQ7 and 12SQ7-GT/G are the same as the 6SQ7 and 6SQ7-GT/G respectively except for heater rating.

12SR7

DUPLEX-DIODE TRIODE

Heater ■	Coated Unipotential Cathode	
Voltage	12.6	a-c or d-c volts
Current	0.15	amp.

The 12SR7 is the same as the 6SR7 except for heater rating.

■ In circuits where the cathode is not directly connected to the heater, the potential difference between heater and cathode should be kept as low as possible.

← Indicates a change.

June 1, 1943

RCA VICTOR DIVISION
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

DATA