Full-Wave Vacuum Rectifier

The	12X4	is	the	sam	e a	st.	he	6 <i>X</i> 2	1 e	xc	:et	t	fo	r	the	following	items:
Heat	er Ch	nara	acte	eris	tic	S	and	d Ra	ati	nç)S:						
	rrent										ę.	8	9	0	a p	0.300	amp
Vo	Itage	e ()	4C c	or D	C)	at	1	eate	er								
i	ampe	res	=0.	300	25	12	29	w 6	æ	4	,p	10	90	s :	s 10	12.6	volts

13CW4

High-Mu Triode

NUVISTOR TYPE

For Use as Grounded-Cathode, Neutralized RF-Amplifier Tube in Tuners of VMF Television and FM Receivers The 13CN4 is the same as the 6CN4 except for the following items: Heater Characteristics and Ratings:

Current. 0.060 amp Voltage (AC or DC) at heater amperes = 0.060 . . .13.5 volts

13**DE**7

Dual Triode

11

With Medium-Mu Unit and Low-Mu Unit

9-PIN MINIATURE TYPE

The 13DE7 is the same as the 6DE7 except for the following items: Heater Characteristics and Ratings: Current. . . . 0.450 ± 0.030 amp Voltage (AC or DC) at heater amperes = 0.450 . . 13.0 volts

sec

Warm-up time (Average) .