

14AF7
TO
14C5



14AF7 MEDIUM-MU TWIN TRIODE

(continued from preceding page)

Amplification Factor	17	16	16	
Plate Resistance	6500	8400	7600	ohms
Transconductance	2600	1900	2100	μ mhos
Plate Current	10.8	5	9	ma

14B6 TWIN DIODE—HIGH-MU TRIODE

Heater, for Unipotential Cathode:

Voltage. 12.6[□] ac or dc volts
Current. 0.15^{□□} amp

The 14B6 is the same as the 7B6 except for heater rating.

[□] Nominal voltage = 14.0 volts. ^{□□} Nominal current = 0.16 ampere.

14B8 PENTAGRID CONVERTER

Heater, for Unipotential Cathode:

Voltage. 12.6[□] ac or dc volts
Current. 0.15^{□□} amp

The 14B8 is the same as the 7B8 except for heater rating.

[□] Nominal voltage = 14.0 volts. ^{□□} Nominal current = 0.16 ampere.

14C5 BEAM POWER AMPLIFIER

Heater, for Unipotential Cathode:

Voltage. 12.6[□] ac or dc volts
Current. 0.225^{□□} amp

The 14C5 is the same as the 7C5 except for heater rating.

[□] Nominal voltage = 14.0 volts. ^{□□} Nominal current = 0.240 ampere.