

14C7
TO
14H7



14E6

TWIN DIODE—MEDIUM-MU TRIODE

Heater, for Unipotential Cathode:

Voltage. 12.6[□] ac or dc volts
Current. 0.15^{□□} amp

The 14E6 is the same as the 7E6 except for heater rating.

□ Nominal voltage = 14.0 volts. □□ Nominal current = 0.16 ampere.

14E7

TWIN DIODE—REMOTE-CUTOFF PENTODE

Heater, for Unipotential Cathodes:

Voltage. 12.6[□] ac or dc volts
Current. 0.15^{□□} amp

The 14E7 is the same as the 7E7 except for heater rating.

□ Nominal voltage = 14.0 volts. □□ Nominal current = 0.16 ampere.

14F7

HIGH-MU TWIN TRIODE

Heater, for Unipotential Cathodes:

Voltage. 12.6[□] ac or dc volts
Current. 0.15^{□□} amp

The 14F7 is the same as the 7F7 except for heater rating.

□ Nominal voltage = 14.0 volts. □□ Nominal current = 0.16 ampere.

14F8

MEDIUM-MU TWIN TRIODE

Heater, for Unipotential Cathode:

Voltage. 12.6[□] ac or dc volts
Current. 0.15^{□□} amp

The 14F8 is the same as the 7F8 except for heater rating.

□ Nominal voltage = 14.0 volts. □□ Nominal current = 0.16 ampere.

14H7

REMOTE-CUTOFF PENTODE

Heater, for Unipotential Cathode:

Voltage. 12.6[□] ac or dc volts
Current. 0.15^{□□} amp

The 14H7 is the same as the 7H7 except for heater rating.

□ Nominal voltage = 14.0 volts. □□ Nominal current = 0.16 ampere.