

17DQ6B

Beam Power Tube

The 17DQ6B is the same as the 6DQ6B except for the following items:

Heater Characteristics and Ratings:

Current.	0.450 ± 0.030	amp
Voltage (AC or DC) at 0.450 amp. . . .	16.8	volts
Warm-up time (Average)	11	sec

17GJ5, 17GJ5A

Beam Power Tube

NOVAR TYPE

The 17GJ5 and 17GJ5A are the same as the 6GJ5 and 6GJ5A, respectively, except for the following items:

Heater Characteristics and Ratings:

Current.	0.450 ± 0.030	amp
Voltage (AC or DC) at 0.450 amp. . . .	16.8	volts
Warm-up time (Average)	11	sec

17GT5A

Beam Power Tube

NOVAR TYPE

The 17GT5A is the same as the 6GT5A except for the following items:

Heater Characteristics and Ratings:

Current.	0.450 ± 0.030	amp
Voltage (AC or DC) at 0.450 amp. . . .	16.8	volts
Warm-up time (Average)	11	sec

17GW6

Beam Power Tube

NOVAR TYPE

The 17GW6 is the same as the 6GW6 except for the following items:

Heater Characteristics and Ratings:

Current.	0.450 ± 0.030	amp
Voltage (AC or DC) at 0.450 amp. . . .	16.8	volts
Warm-up time (Average)	11	sec

