

17JB6, 17JB6A

Beam Power Tube

NOVAR TYPE

The 17JB6 and 17JB6A are the same as the 6JB6 and 6JB6A, respectively, except for the following items:

Heater Characteristics and Ratings:

Current.	0.450 ± 0.030	amp
Voltage (AC or DC) at 0.450 amp.	16.8	volts
Warm-up time (Average)	11	sec

17JG6, 17JG6A

Beam Power Tube

NOVAR TYPE

The 17JG6 and 17JG6A are the same as the 6JG6 and 6JG6A, respectively, except for the following items:

Heater Characteristics and Ratings:

Current.	0.600 ± 0.040	amp
Voltage (AC or DC) at 0.600 amp.	16.8	volts
Warm-up time (Average)	11	sec

17JT6, 17JT6A

Beam Power Tube

NOVAR TYPE

The 17JT6 and 17JT6A are the same as the 6JT6 and 6JT6A, respectively, except for the following items:

Heater Characteristics and Ratings:

Current.	0.450 ± 0.030	amp
Voltage (AC or DC) at 0.450 amp.	16.8	volts
Warm-up time (Average)	11	sec

17JZ8

Medium-Mu Triode—Beam Power Tube

DUODECAR TYPE

The 17JZ8 is the same as the 6JZ8 except for the following items:

Heater Characteristics and Ratings:

Current.	0.450 ± 0.030	amp
Voltage (AC or DC) at 0.450 amp.	16.8	volts
Warm-up time (Average)	11	sec

