## Medium-Mu Triode— Beam Power Tube

### Duodecar Type

The 17JZ8 is the same as the 6JZ8 except for:

#### Heater Characteristics and Ratings

Current .				9 8 8 8		$0.450 \pm 0.030$	A
Voltage (a	ae or de)	at 0.450	Α.	* * * *	p 8	16.8	V
Warm-up ti	me (Ave	cage)	8 0 0	0 0 2 0	0 0	American American	S

# 17KV6

### **Beam Power Tube**

### Novar Type

The 17KV6 is the same as the 6KV6 except for:

#### Heater Characteristics and Ratings

Current	. 8	e 0	6 8	8 0	. 8	6 0	99	4	ø	ŧ	s	ą.	8		6	$0.600 \pm 0.040$	A
Voltage	(ac	Oľ	dc)	at	0.6	30C	A		0	9	0	8	9	8	6	16.8	V
Warm-up	time	e (2	Ave	rage	)		*	g	.00	o	4	ø	8	8	p		8

## 17KV6A

### **Beam Power Tube**

#### **Novar Type**

The 17KV6A is the same as the 6KV6A except for:

#### Heater Characteristics and Ratings

Current	0.600 ± 0.040	A
Voltage (ac or dc) at 0.600A	16.8	V
Warm-up time (Average)	11	s