Medium-Mu Triode— Beam Power Tube

Duodecar Type

The 17JZ8 is the same as the 6JZ8 except for:

Heater	Chara	cteristics	and	Ratinas
--------	-------	------------	-----	---------

Current		* 0	6 0	e s	n c	9 R R	÷	٥	-03	Q2	86	6)-		8	ø	0.450 ± 0.030	A
Voltage	(ac	or	de)	at	0.	450	A	À.	a	n	8	*	ão.	10	8	16.8	V
Warm-up	tim	e (/	Ave	rage)	8 6	8	Ф	8	ø	ę.	2	ds.	g)	a	11	S

17KV6

Beam Power Tube

Novar Type

The 17KV6 is the same as the 6KV6 except for:

Heater Characteristics and Ratings

Current 0.600 \pm 0.040	A
Voltage (ac or dc) at 0.600A 16.8	V
Warm-up time (Average) 11	s

17KV6A

Beam Power Tube

Novar Type

The 17KV6A is the same as the 6KV6A except for:

Heater Characteristics and Ratings

Current	0 9	0 0	8 9	0 \$	8 8	0 6	9	8	ø	8	0	s	a	8	86	U.0UU _ U.U4U	23.
Voltage	(ac	or	dc)	at	0.	600	A		ø	ø	ė	٠	5	9	0	16.8	V
Warm-up	tim	e (/	Ave	rage)		0	0	0	÷	9	4	c	ø	Ф		S